

# Product datasheet

Specifications



## 250A 3P+N switch disconnecter

Local distributor code:

392061854

MGE2503XS

⚠ Discontinued on: 15 Feb 2023

EAN Code: 5018934934198

⚠ Discontinued

### Main

Range	SafePacT 2
Product or component type	Enclosed switch-disconnector
Poles description	3P + N
[In] rated current	250 A at 40 °C
[Ue] rated operational voltage	415 V AC 50/60 Hz
Suitability for isolation	Yes
Utilisation category	AC-23
Contact position indicator	Yes
Control type	Toggle

### Complementary

Earth-leakage protection	Without
Enclosure material	Steel epoxy-polyester powder cream
Mechanical durability	20000 cycles
Electrical durability	20000 cycles In/2 10000 cycles In

### Environment

IP degree of protection	IP42 conforming to IEC 60529
-------------------------	------------------------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

### Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

EU RoHS Directive

[Compliant](#)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins