

Product datasheet

Specifications



Plug in relay, Zelio Relay, RHK, latching, 4 C/O, 42 V AC 50 Hz, 5 A

RHK411D

⚠ Discontinued on: 22 Apr 2021

⚠ Discontinued

Main

Range of product	Harmony Relay
Product or component type	Plug-in relay
Device short name	RHK
Contacts type and composition	4 C/O
Contact operation	Standard Latching
[Uc] control circuit voltage	42 V AC 50 Hz
[Ithe] conventional enclosed thermal current	5 A 40 °C
status LED	Without
Control type	Manual control
Coil interference suppression	Without

Complementary

[Ui] rated insulation voltage	250 V
Operating position	Any position
Minimum switching capacity	150 mVA at 10 mA 150 mVA, 1 V
Contact bounce time	<= 10 ms
Maximum voltage drop	<100 V for 3 A at 24 V
Average resistance	30 mOhm at 20 °C
Average coil consumption in VA	6 (inrush) on coil 1 1.3 (holding) on coil 2 2.5 (inrush) on coil 2 3.5 (holding) on coil 1
Control circuit voltage limits	0.8...1.1 Uc conforming to IEC 60255
Drop-out voltage threshold	0.15...0.5 Uc
Cos phi	0.6 (inrush) 0.7 (holding)
Mechanical durability	10000000 cycles
maximum operating rate	2 cyc/mn
Operating time	5...17 ms between energisation of coil and closing of NO contact at 20 °C 8...16 ms between energisation of trip coil and closing of NC contact at 20 °C 1...3 ms for energisation/de-energisation 0.5...6 ms for de-energisation/energisation
Minimum pulse duration	50 ms

CAD overall width	33 mm
CAD overall height	43 mm
CAD overall depth	90 mm
Terminals description ISO n°1	(21-22-24)OC (31-32-34)OC (A1-A2)CO (41-42-44)OC (11-12-14)OC (B1-B2)CO
Net weight	0.14 kg
Compatibility code	RHK

Environment

Standards	NF C 45-250 VDE 0435 IEC 255 BS 4794
Product certifications	USSR UR ASE EDF CSA BV
Protective treatment	TC
Dielectric strength	2500 V
Ambient air temperature for operation	-5...40 °C conforming to IEC 60255
Ambient air temperature for storage	-40...70 °C
Vibration resistance	6 gn (f= 10...55 Hz) conforming to IEC 60068-2-6 6 gn (f= 10...55 Hz) conforming to NF C 20-616
Shock resistance	30 gn for 11 ms conforming to NF C 20-608

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	5 cm
Package 1 Length	11.5 cm
Package 1 Weight	155 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins