

# Product datasheet

Specifications



## Contactor, TeSys Deca, 3P(3NO), AC-3/AC-3e, <=440V, 12A, 72V DC coil, lugs-ring terminals

LC1D126SD

⚠ Discontinued on: 1 Dec 2024

⚠ To be discontinued

### Main

|                                |                                                                                                                                                                             |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product               | TeSys Deca                                                                                                                                                                  |
| Product or component type      | Contactor                                                                                                                                                                   |
| Device short name              | LC1D                                                                                                                                                                        |
| Contactor application          | Motor control<br>Resistive load                                                                                                                                             |
| Utilisation category           | AC-1<br>AC-4<br>AC-3<br>AC-3e                                                                                                                                               |
| Poles description              | 3P                                                                                                                                                                          |
| [Ue] rated operational voltage | Power circuit: <= 690 V AC 25...400 Hz<br>Power circuit: <= 300 V DC                                                                                                        |
| [Ie] rated operational current | 25 A (at <60 °C) at <= 440 V AC AC-1 for power circuit<br>12 A (at <60 °C) at <= 440 V AC AC-3 for power circuit<br>12 A (at <60 °C) at <= 440 V AC AC-3e for power circuit |
| [Uc] control circuit voltage   | 72 V DC                                                                                                                                                                     |

### Complementary

|                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Motor power kW                              | 3 kW at 220...230 V AC 50/60 Hz (AC-3)<br>5.5 kW at 380...400 V AC 50/60 Hz (AC-3)<br>5.5 kW at 415...440 V AC 50/60 Hz (AC-3)<br>7.5 kW at 500 V AC 50/60 Hz (AC-3)<br>7.5 kW at 660...690 V AC 50/60 Hz (AC-3)<br>3.7 kW at 400 V AC 50/60 Hz (AC-4)<br>3 kW at 220...230 V AC 50/60 Hz (AC-3e)<br>5.5 kW at 380...400 V AC 50/60 Hz (AC-3e)<br>5.5 kW at 415...440 V AC 50/60 Hz (AC-3e)<br>7.5 kW at 500 V AC 50/60 Hz (AC-3e)<br>7.5 kW at 660...690 V AC 50/60 Hz (AC-3e) |
| Motor power hp                              | 0.5 hp at 115 V AC 50/60 Hz for 1 phase motors<br>2 hp at 230/240 V AC 50/60 Hz for 1 phase motors<br>3 hp at 200/208 V AC 50/60 Hz for 3 phases motors<br>3 hp at 230/240 V AC 50/60 Hz for 3 phases motors<br>7.5 hp at 460/480 V AC 50/60 Hz for 3 phases motors<br>10 hp at 575/600 V AC 50/60 Hz for 3 phases motors                                                                                                                                                       |
| Compatibility code                          | LC1D                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Pole contact composition                    | 3 NO                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Protective cover                            | With                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| [Ith] conventional free air thermal current | 25 A (at 60 °C) for power circuit<br>10 A (at 60 °C) for signalling circuit                                                                                                                                                                                                                                                                                                                                                                                                     |
| Irms rated making capacity                  | 250 A at 440 V for power circuit conforming to IEC 60947<br>140 A AC for signalling circuit conforming to IEC 60947-5-1<br>250 A DC for signalling circuit conforming to IEC 60947-5-1                                                                                                                                                                                                                                                                                          |

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Rated breaking capacity</b>                  | 250 A at 440 V for power circuit conforming to IEC 60947                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>[Icw] rated short-time withstand current</b> | 105 A 40 °C - 10 s for power circuit<br>210 A 40 °C - 1 s for power circuit<br>30 A 40 °C - 10 min for power circuit<br>61 A 40 °C - 1 min for power circuit<br>100 A - 1 s for signalling circuit<br>120 A - 500 ms for signalling circuit<br>140 A - 100 ms for signalling circuit                                                                                                                                                                                                                                                               |
| <b>Associated fuse rating</b>                   | 10 A gG for signalling circuit conforming to IEC 60947-5-1<br>40 A gG at <= 690 V coordination type 1 for power circuit<br>25 A gG at <= 690 V coordination type 2 for power circuit                                                                                                                                                                                                                                                                                                                                                               |
| <b>Average impedance</b>                        | 2.5 mOhm - lth 25 A 50 Hz for power circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Power dissipation per pole</b>               | 0.36 W AC-3<br>1.56 W AC-1<br>0.36 W AC-3e                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>[Ui] rated insulation voltage</b>            | Power circuit: 690 V conforming to IEC 60947-4-1<br>Power circuit: 600 V CSA certified<br>Power circuit: 600 V UL certified<br>Signalling circuit: 690 V conforming to IEC 60947-1<br>Signalling circuit: 600 V CSA certified<br>Signalling circuit: 600 V UL certified                                                                                                                                                                                                                                                                            |
| <b>Overvoltage category</b>                     | III                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Pollution degree</b>                         | 3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>[Uimp] rated impulse withstand voltage</b>   | 6 kV conforming to IEC 60947                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Safety reliability level</b>                 | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Mechanical durability</b>                    | 30 Mcycles                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Electrical durability</b>                    | 2 Mcycles 12 A AC-3 at Ue <= 440 V<br>0.8 Mcycles 25 A AC-1 at Ue <= 440 V<br>2 Mcycles 12 A AC-3e at Ue <= 440 V                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Control circuit type</b>                     | DC standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Coil technology</b>                          | With integral suppression device                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Control circuit voltage limits</b>           | 0.1...0.25 Uc (-40...70 °C):drop-out DC<br>0.7...1.25 Uc (-40...60 °C):operational DC<br>1...1.25 Uc (60...70 °C):operational DC                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Inrush power in W</b>                        | 5.4 W (at 20 °C)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Hold-in power consumption in W</b>           | 5.4 W at 20 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Operating time</b>                           | 63 ±15 % ms closing<br>20 ±20 % ms opening                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Time constant</b>                            | 28 ms                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Maximum operating rate</b>                   | 3600 cyc/h at 60 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Connections - terminals</b>                  | Control circuit: lugs-ring terminals - external diameter: 8 mm<br>Power circuit: lugs-ring terminals - external diameter: 8 mm                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Tightening torque</b>                        | Control circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver flat Ø 6 mm M3.5<br>Control circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver Philips No 2 M3.5<br>Power circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver flat Ø 8 mm M3.5<br>Power circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver Philips No 2 M3.5<br>Control circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver pozidriv No 2 M3.5<br>Power circuit: 1.7 N.m - on lugs-ring terminals - with screwdriver pozidriv No 2 M3.5 |
| <b>Auxiliary contact composition</b>            | 1 NO + 1 NC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Auxiliary contacts type</b>                  | type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1<br>type mirror contact 1 NC conforming to IEC 60947-4-1                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Signalling circuit frequency</b>             | 25...400 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Minimum switching voltage</b>                | 17 V for signalling circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

|                           |                                                                                                         |
|---------------------------|---------------------------------------------------------------------------------------------------------|
| Minimum switching current | 5 mA for signalling circuit                                                                             |
| Insulation resistance     | > 10 MOhm for signalling circuit                                                                        |
| Non-overlap time          | 1.5 ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact |
| Mounting support          | Rail<br>Plate                                                                                           |

## Environment

|                                                       |                                                                                                                                                                                                             |
|-------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standards                                             | CSA C22.2 No 14<br>EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 60947-4-1<br>IEC 60335-1:Clause 30.2<br>IEC 60335-2-40:Annex JJ<br>UL 60335-2-40:Annex JJ<br>CSA C22.2 No 60947-4-1 |
| Product certifications                                | UL<br>CCC<br>CSA<br>Marine<br>UKCA<br>EAC<br>CB Scheme                                                                                                                                                      |
| IP degree of protection                               | IP20 front face conforming to IEC 60529                                                                                                                                                                     |
| Protective treatment                                  | TH conforming to IEC 60068-2-30                                                                                                                                                                             |
| Climatic withstand                                    | conforming to IACS E10 exposure to damp heat<br>conforming to IEC 60947-1 Annex Q category D exposure to damp heat                                                                                          |
| Permissible ambient air temperature around the device | -40...60 °C<br>60...70 °C with derating                                                                                                                                                                     |
| Operating altitude                                    | 0...3000 m                                                                                                                                                                                                  |
| Fire resistance                                       | 850 °C conforming to IEC 60695-2-1                                                                                                                                                                          |
| Flame retardance                                      | V1 conforming to UL 94                                                                                                                                                                                      |
| Mechanical robustness                                 | Vibrations contactor open (2 Gn, 5...300 Hz)<br>Vibrations contactor closed (4 Gn, 5...300 Hz)<br>Shocks contactor open (10 Gn for 11 ms)<br>Shocks contactor closed (15 Gn for 11 ms)                      |
| Height                                                | 77 mm                                                                                                                                                                                                       |
| Width                                                 | 45 mm                                                                                                                                                                                                       |
| Depth                                                 | 95 mm                                                                                                                                                                                                       |
| Net weight                                            | 0.485 kg                                                                                                                                                                                                    |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 10.3 cm |
| Package 1 Width              | 8.1 cm  |
| Package 1 Length             | 5.4 cm  |
| Package 1 Weight             | 501.0 g |

## Contractual warranty

---

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 37 kg CO2 eq.                                 |
| Carbon footprint of the manufacturing phase [A1 to A3] | 3 kg CO2 eq.                                  |
| Carbon footprint of the distribution phase [A4]        | 0.1 kg CO2 eq.                                |
| Carbon footprint of the installation phase [A5]        | 0 kg CO2 eq.                                  |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 33 kg CO2 eq.                                 |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 1 kg CO2 eq.                                  |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                                        |                                                                                        |
|----------------------------------------|----------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes                                                                                    |
| Packaging without single use plastic   | Yes                                                                                    |
| SCIP Number                            | 50ae7612-fd2e-41e4-a369-50d0dea6e592                                                   |
| EU RoHS Directive                      | <a href="#">Compliant By Exemption</a>                                                 |
| REACH Regulation                       | <a href="#">Reference contains Substances of Very High Concern above the threshold</a> |
| PVC free                               | Yes                                                                                    |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                                 |                                                                                                                                                                                                                 |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in %   | 75                                                                                                                                                                                                              |
| End of life manual availability | <a href="#">End of Life Information</a>                                                                                                                                                                         |
| Take-back                       | Nej                                                                                                                                                                                                             |
| WEEE Label                      |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Offer Marketing Illustration

Product benefits / Features



## TeSys Deca Contactors

### Range Accessories



Auxiliary contact block



Time delay auxiliary contact block



Mechanical interlock



Comb busbar



Assembling kits



Power connections



Contactor Coil

Offer Marketing Illustration

Product benefits / Features

### TeSys Deca Contactors



**Reliable**

Multi-standard solutions, high reliability, long mechanical and electrical durability for different sizes, and the most complete accessories.



**Energy efficiency**

These electronic-coil contactors require up to 80 % less energy than electro-mechanical contactors.



**Universal**

Multi standards certified (IEC, UL, CSA, CCC, EAC, Marine), Green Premium compliant (RoHS/REACH).



25 Feb 2026

Life Is On | Schneider Electric

7

Offer Marketing Illustration

Product benefits / Features



The image shows a TeSys Deca Contactor, model LC1D09, which is a black industrial-grade device. It features a green label with the 'TeSys' and 'Schneider Electric' logos. The device has multiple terminals on top and bottom, labeled with numbers and letters (e.g., 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100). The device is shown against a green circular background.

### TeSys Deca Contactors



#### Technical Benefits


- Deca green delivers a consistent low consumption range of contactors from 9 A to 80 A.
- Covers control voltage from 24 to 250 V, with same coils for AC and DC.
- Designed to meet the requirements of industrial and HVAC applications
- With IEC60335-1 compliance, improved fire resistance, and dust-proof auxiliaries
- Suitable for safety applications thanks to mechanically linked contacts and mirror contacts
- Outstanding breaking/making capacity up to 20 In with PLC direct connection

Image of product / Alternate images

Alternative

---





Technical Illustration

Assembly's dimensions

