



D4SL-N4AFG










Guard lock safety-door switch, D4SL-N, M20, 1NC/1NO + 1NC/1NO, head: resin, 24VDC solenoid lock/mechanical release

Specifications

Door switch type	Key-operated
Guard-lock	✓
Material housing	Plastic
Material head	Resin
Ambient temperature (operating)	-10-55 °C
Holding force	1300 N
Direction of operation	Adjustable
Door contacts NC	1
Door contacts NO	1
Lock monitor contacts NC	1
Lock monitor contacts NO	1
Lock/Release key type	Standard key
Lock/Release key position	Front + Back
Lock/Release key material	Metal
Solenoid voltage	24 V
With LED indicator	✗
Connection method	System connector
Cable length	0 m
Degree of protection (IP)	IP67
Conduit size	M20
Number of conduits	1
Shape	Cuboid
Overall length	155 mm

Height of sensor	39 mm
Width sensor	39 mm
Lock/Release logic	Power to lock (Solenoid lock)

Accessories

	D4SL-NK1	Operation key for D4SL-N; horizontal mounting
	D4SL-NK1G	Operation key for D4SL-N; horizontal mounting, cushion rubber
	D4SL-NK1S	Operation key for D4SL-N; horizontal mounting, no cushion rubber (short type)
	D4SL-NK2	Operation key for D4SL-N; vertical mounting
	D4SL-NK2G	Operation key for D4SL-N; vertical mounting, cushion rubber
	D4SL-NK3	Operation key for D4SL-N; adjustable mounting (horizontal)
	D4SL-NK5	Operation key for D4SL-N; adjustable (horizontal/vertical)
	D4SL-NSK10-LK	D4SL-N slide/lockout key system, without inner lever
	D4SL-NSK10-LKH	D4SLN slide/lockout key system, with inner lever

CAD Library



D4SL-N Guard Lock Safety-door Switch Datasheet

EN PDF 4.14 MB



Machine Safety Catalogue

EN PDF 9.91 MB



Machine Safety Solution Brochure

EN PDF 2.86 MB



Safety Component Selection Guide Brochure

EN PDF 10.8 MB



Safety Interlock Switches Brochure

EN PDF 1.52 MB



Safety Solution Advanced Guide Guide

EN PDF 2.57 MB



Safety Solution Basic Guide Guide

EN PDF 14.4 MB