

Product data sheet

Specifications



coil WB1-K - 127 V AC 50 Hz for CV1B Contactor

WB1KB166

⚠ Discontinued on: May 19, 2023

⚠ Discontinued

Important message: This product is no longer commercialized by Schneider Electric. As per 14 January 2022, the commercialization is managed by Lenoir Elec. Please follow the link <https://www.lenoir-elec.com/> for more details.

Main

Range	TeSys
Product or Component Type	Contacteur coil
Range compatibility	TeSys TeSys B CV1BJ contactor TeSys TeSys B CV1BL contactor
Control circuit type	AC
Coil type	Low consumption
[Uc] control circuit voltage	127 V AC 50 Hz

Complementary

Control circuit voltage limits	Operational: 0.85...1.1 Uc at 50 Hz (at <131 °F (55 °C))
Average resistance	0.59 Ohm 68 °F (20 °C)
Inductance of closed circuit	0.228 H
Inrush power in VA	2300...3060 VA 50 Hz 0.14 68 °F (20 °C))
Inrush power in W	320...430 W 68 °F (20 °C)
Hold-in power consumption in VA	205...385 VA 50 Hz 0.36 68 °F (20 °C))
Hold-in power consumption in W	65...140 W 68 °F (20 °C)
Net Weight	2.47 lb(US) (1.12 kg)

Ordering and shipping details

Category	18402-WORLD SERVICE PARTS(CONTROL ACCESS)
Discount Schedule	CP10
GTIN	3389110479768
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.7 in (9.5 cm)
Package 1 Width	2.8 in (7 cm)
Package 1 Length	6.7 in (17 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package weight(Lbs)	2.493 lb(US) (1.131 kg)
---------------------	-------------------------

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.