

## Data sheet for SINAMICS Basic Operator Panel (BOP-2)

Article No. : 6SL3255-0AA00-4CA1



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Screen |  |
|--------|--|
|--------|--|

|                |                 |
|----------------|-----------------|
| Display design | LCD, monochrome |
|----------------|-----------------|

| Mechanical data |  |
|-----------------|--|
|-----------------|--|

|                      |                   |
|----------------------|-------------------|
| Degree of protection | IP55 / UL type 12 |
|----------------------|-------------------|

|            |                    |
|------------|--------------------|
| Net weight | 0.140 kg (0.31 lb) |
|------------|--------------------|

Dimensions

|        |                     |
|--------|---------------------|
| Width  | 70.00 mm (2.76 in)  |
| Height | 106.85 mm (4.21 in) |
| Depth  | 19.60 mm (0.77 in)  |

| Ambient conditions |  |
|--------------------|--|
|--------------------|--|

Ambient temperature

|           |                             |
|-----------|-----------------------------|
| Operation | 0 ... 50 °C (32 ... 122 °F) |
|-----------|-----------------------------|

|         |                                |
|---------|--------------------------------|
| Storage | -40 ... 70 °C (-40 ... 158 °F) |
|---------|--------------------------------|

|           |                                |
|-----------|--------------------------------|
| Transport | -40 ... 70 °C (-40 ... 158 °F) |
|-----------|--------------------------------|

Relative humidity at 25°C during

|                |      |
|----------------|------|
| Max. operation | 95 % |
|----------------|------|

| Approvals |  |
|-----------|--|
|-----------|--|

|                            |                          |
|----------------------------|--------------------------|
| Certificate of suitability | CE, cULus, EAC, KCC, RCM |
|----------------------------|--------------------------|