

Product datasheet

Specifications



AC / DC power adapter for HMIPSO and HMIDAD

HMIYPSOMAC1

⚠ To be discontinued on: 30 Apr 2029

⚠ To be discontinued

Main

Range of product	Harmony iPC
Product or component type	External power supply module
Accessory / separate part category	Electrical accessory

Complementary

Accessory / separate part destination	HMIDAD Harmony iPC HMIPSP S-Panel PC performance HMIPSO S-Panel PC
Input voltage	90...260 V AC at 47...63 Hz
Input current	1600 mA at 100 V AC
Output voltage	24 V DC
[In] rated current	2.62 A
Inrush current	70 A at 230 V AC

Environment

Ambient air temperature for operation	0...70 °C
Ambient air temperature for storage	-40...85 °C
Relative humidity	0...95 % non-condensing
Product certifications	CE CSA 60950 cULus UL 60950

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.45 cm
Package 1 Width	5.2 cm
Package 1 Length	11.8 cm
Package 1 Weight	600 g
Unit Type of Package 2	S04
Number of Units in Package 2	3
Package 2 Height	30 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	2.97 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
F-gas free	K izolaci a zhášení je využíváno pouze vzduchové a vakuové médium; bez obsahu F-plynů včetně SF6.
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	1d4618f5-6af2-476b-9c12-08aec44ed716
Halogen-free status	Product contains halogen above thresholds
PVC free	No
Silicone-free	No

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins