

Product data sheet

Specifications



STS60 - Wall - Ball screw 200 - ARMIO Board with user I/O cable

LXMSTS60W2A2000

! Discontinued on: Sep 15, 2023

! End-of-service on: Dec 31, 2024

! Discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	PacDrive 3
Product or Component Type	SCARA robot
Device short name	STS60

Complementary

Number of axis	4
Operating position	Rotational 360°
Operating travel	0...7.9 in (0...200 mm) vertical 0...47.2 in (0...1200 mm) horizontal
Repeat accuracy	+/- 0.01 mm
Permanent permissible load	17.6 lb(US) (8 kg)
Nominal speed	2000 mm/s axis 3 6.39 m/s axis 1 6.39 m/s axis 2
Maximum actuation speed	2220 mm/s axis 3 26.28 ft/s (8.01 m/s) axis 1 26.28 ft/s (8.01 m/s) axis 2
Angular speed	1200°/s nominal axis 4 1929°/s maximum axis 4 385°/s nominal axis 1 490°/s maximum axis 1 500°/s nominal axis 2 610°/s maximum axis 2
Net Weight	118.4 lb(US) (53.7 kg)
Range Compatibility	Lexium 62 motor

Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

Ordering and shipping details

Category	US1PC5218357
Discount Schedule	PC52
GTIN	3606489594138
Returnability	No

Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	43.3 in (110.0 cm)
Package 1 Width	28.0 in (71.0 cm)
Package 1 Length	31.5 in (80.0 cm)
Package weight(Lbs)	154.3 lb(US) (70.0 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No