

Product datasheet

Specifications



Output shorting link, GoPact MTS 2000, 1250A

GMSCONOSL0612H

Main

Range of product	GoPact MTS
Product or component type	Shorting link
Device application	Connection
Range compatibility	GoPact MTS 2000
[In] rated current	1250 A
Frame size	6
Quantity per set	4 pieces

Complementary

Connections - terminals	Bolted connection
-------------------------	-------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.5 cm
Package 1 Width	14.1 cm
Package 1 Length	18.7 cm
Package 1 Weight	3.02 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Packaging

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Take-back	No
-----------	----

Technical Illustration

Assembly's dimensions

