


Product data sheet

Specifications



TeSys F - specific contactor coil - 500 V AC 40...400 Hz low consumption

LX9FH5002

⚠ Discontinued on: Jul 12, 2021

⚠ Discontinued

Main

Range	TeSys
Product or Component Type	Specific contactor coil
Device short name	LX9FH
Range compatibility	TeSys TeSys F LC1F contactor
Product Compatibility	LC1F265 LC1F330
Control circuit type	AC 40...400 Hz low consumption
[Uc] control circuit voltage	500 V AC 40...400 Hz
Average resistance	345 Ohm inrush 68 °F (20 °C) 7990 Ohm holding 68 °F (20 °C)
Operating time	25 ms opening 45 ms closing
Mechanical durability	10 Mcycles
Maximum operating rate	3600 cyc/h 131 °F (55 °C)

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Operational 0.85...1.1 Uc 131 °F (55 °C)) Drop-out 0.35...0.55 Uc 131 °F (55 °C))
Inrush power in VA	560...660 VA 40...400 Hz (at 68 °F (20 °C))
Hold-in power consumption in VA	8...10 VA 40...400 Hz (at 68 °F (20 °C))
Heat dissipation	8.4...10.4 W

Environment

Ambient Air Temperature for Operation	23...131 °F (-5...55 °C)
Net Weight	1.65 lb(US) (0.75 kg)

Ordering and shipping details

Category	22341-CONTACTOR,D,K,&F ACCESS
Discount Schedule	I12
GTIN	3389110454734
Returnability	No
Country of origin	CZ

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.5 in (9 cm)
Package 1 Width	3.9 in (10 cm)
Package 1 Length	7.5 in (19 cm)
Package weight(Lbs)	30.7 oz (870 g)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better



Materials and Substances

[EU RoHS Directive](#)

Pro-active compliance (Product out of EU RoHS legal scope)

Use Longer



Lifetime extension

[Repair](#)

[No](#)