

Data sheet for SINAMICS G120D

Article No. : 6SL3546-0FB21-1FB0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :



Figure similar

Electrical data

Operating voltage via

External power supply	DC 24 V
-----------------------	---------

Communication

Communication	PROFINET, EtherNet/IP, PROFIsave
---------------	----------------------------------

Inputs / outputs

Standard digital inputs

Number	6 (non-isolated)
--------	------------------

Fail-safe digital inputs

Number	3 (optionally parameterizable as safe inputs)
--------	---

Digital outputs

Number	2 (0.5 A, fed through switched 24 V DC, isolated)
--------	---

Fail-safe digital outputs

Number	1 (optionally parameterizable as safe digital output)
--------	---

Closed-loop control techniques

V/f linear / square-law / parameterizable	Yes
---	-----

V/f with flux current control (FCC)	Yes
-------------------------------------	-----

Sensorless vector control	Yes
---------------------------	-----

Ambient conditions

Ambient temperature

Operation	0 ... 50 °C (32 ... 122 °F)
-----------	-----------------------------

Storage	-40 ... 70 °C (-40 ... 158 °F)
---------	--------------------------------

Relative humidity

Max. operation	95 % at 40 °C (104 °F); RH, condensation not permitted
----------------	--

Technology

Positioning functionality	Yes
---------------------------	-----

Design of the interface	push-pull plug
-------------------------	----------------

Mechanical data

Degree of protection	IP65 / UL type 3
----------------------	------------------

Net weight	1.3 kg (2.87 lb)
------------	------------------

Dimensions

Width	153 mm (6.02 in)
-------	------------------

Height	208 mm (8.19 in)
--------	------------------

Depth	118 mm (4.65 in)
-------	------------------