

Product datasheet

Specifications



Mini contactor, TeSys SK, 2P(2NO), AC-3, 690V 5A, 220V AC coil

LC1SKGC200M7

Main

Range	TeSys
Product name	TeSys SK
Product or component type	Mini contactor
Device short name	LC1SKGC
Contactor application	Motor control Resistive load
Utilisation category	AC-1 AC-3
power pole contact composition	2P
Pole contact composition	2 NO
[Ie] rated operational current	5 A at ≤ 400 V AC AC-3 20 A (at ≤ 50 °C) AC AC-1
[Ue] rated operational voltage	Power circuit: 690 V AC 50/60 Hz

Complementary

Control circuit type	AC at 50/60 Hz
[Uc] control circuit voltage	220 V AC 50/60 Hz
[Ith] conventional free air thermal current	20 A (at 55 °C) for power circuit
Irms rated making capacity	50 A AC conforming to NF C 63-110 50 A AC conforming to IEC 60947
Rated breaking capacity	40 A at ≤ 400 V conforming to NF C 63-110 40 A at ≤ 400 V conforming to IEC 60947
[Icw] rated short-time withstand current	40 A 55 °C for power circuit
Associated fuse rating	20 A gI at ≤ 440 V for power circuit
Average impedance	4 mOhm - Ith 20 A 50 Hz for power circuit
[Ui] rated insulation voltage	Power circuit: 690 V conforming to BS 5424 Power circuit: 690 V conforming to IEC 60947 Power circuit: 690 V conforming to UL 508 Power circuit: 690 V conforming to VDE 0110 group C Power circuit: 690 V conforming to CSA C22.2 No 14
Mounting support	Rail
Standards	EN/IEC 60947-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
Product certifications	CB Scheme CE UKCA EAC cULus

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Connections - terminals	Connector 1 cable(s) 1.5...6 mm ² solid Connector 2 cable(s) 1.5...4 mm ² solid Connector 1 cable(s) 0.5...6 mm ² flexible without cable end Connector 2 cable(s) 0.35...2.5 mm ² flexible without cable end Connector 1 cable(s) 0.35...6 mm ² flexible with cable end Connector 2 cable(s) 0.35...1.5 mm ² flexible with cable end
Tightening torque	Power circuit: 0.8 N.m - on connector - with screwdriver pozidriv No 1
Operating time	6...8 ms coil de-energisation and NO opening 7...14 ms coil energisation and NO closing
Mechanical durability	10 Mcycles
Maximum operating rate	1200 cyc/h
Control circuit voltage limits	Operational: 0.85...1.1 Uc at 50/60 Hz (at <55 °C) Drop-out: 0.2...0.75 Uc at 50/60 Hz (at <55 °C)
Inrush power in VA	16 VA 50/60 Hz (at 20 °C)
Hold-in power consumption in VA	4.2 VA 50/60 Hz (at 20 °C)
Heat dissipation	1.4 W at 50/60 Hz

Environment

IP degree of protection	IP2X conforming to VDE 0106
Protective treatment	TC conforming to IEC 60068 TC conforming to DIN 50015
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-50...70 °C
Operating altitude	2000 m without derating
Height	56 mm
Width	27 mm
Depth	55.5 mm
Net weight	0.132 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.200 cm
Package 1 Width	6.000 cm
Package 1 Length	6.800 cm
Package 1 Weight	121.700 g
Unit Type of Package 2	S01
Number of Units in Package 2	40
Package 2 Height	15.000 cm
Package 2 Width	15.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	5.067 kg
Unit Type of Package 3	P06
Number of Units in Package 3	1280
Package 3 Height	75.000 cm

Package 3 Width	80.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	170.134 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	52 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.7 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	51 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	C39a7e5e-6a28-4540-b3bb-b5a727bdce6a
REACH Regulation	REACH Declaration

Use Longer




Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	64
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

Assembly's dimensions

