

Product data sheet

Specifications



SH3 servomotor, 140mm, 4 stacks,
smooth Shaft, SinCos Singleturn
128, no Brake, angular, IP65/67

SH31404P01A2200

⚠ Discontinued on: Oct 11, 2021

⚠ Discontinued

Main

Range Compatibility	PacDrive 3
Device short name	SH3
Product or Component Type	Servo motor

Complementary

Maximum mechanical speed	4000 rpm
[Us] rated supply voltage	115...480 V
Phase	Three phase
Continuous stall current	21.3 A
Continuous stall torque	295.6 lbf.in (33.4 N.m) 115...480 V three phase
Continuous power	4040 W
Peak stall torque	1167.4 lbf.in (131.9 N.m) 115...480 V three phase
Nominal output power	2370 W 115 V single phase 4130 W 230 V single phase 4040 W 400 V three phase 4190 W 480 V three phase
Nominal torque	267.3 lbf.in (30.2 N.m) 115 V single phase 232.8 lbf.in (26.3 N.m) 230 V single phase 114.2 lbf.in (12.9 N.m) 400 V three phase 98.2 lbf.in (11.1 N.m) 480 V three phase
Nominal speed	750 rpm 115 V single phase 1500 rpm 230 V single phase 3000 rpm 400 V three phase 3600 rpm 480 V three phase
Maximum current Irms	95.6 A
Shaft end	Smooth shaft
Shaft diameter	0.9 in (24 mm)
Shaft length	2.0 in (50 mm)
IP degree of protection	IP65 motor: conforming to IEC 60034-5 IP65 shaft bushing: conforming to IEC 60034-5 IP67 housing: conforming to IEC 60034-5
Encoder type	Absolute single turn SinCos Hiperface
Speed feedback resolution	128 periods
Holding brake	Without
Mounting Support	International standard flange
Motor flange size	5.5 in (140 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Electrical Connection	Rotatable right angled connector
Torque constant	1.57 N.m/A 248 °F (120 °C)
Back emf constant	104 V/krpm 68 °F (20 °C)
Number of motor poles	5
Rotor inertia	23.7 kg.cm²
Stator resistance	0.28 Ohm
Stator inductance	5.945 mH
Maximum radial force Fr	2660 N 1000 rpm 2110 N 2000 rpm 1840 N 3000 rpm
Maximum axial force Fa	300 N
Type of cooling	Natural convection
Length	15.06 in (382.5 mm)
Centring collar diameter	5.1 in (130 mm)
Centring collar depth	0.1 in (3.5 mm)
Number of mounting holes	4
Mounting holes diameter	0.4 in (11 mm)
Circle diameter of the mounting holes	6.5 in (165 mm)
Net Weight	57.3 lb(US) (26 kg)
Sizing reference	SH31404P
Network number of phases	3
Temperature copper hot	266 °F (130 °C)
Electrical connection	rotatable right angled connector

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.4 in (1 cm)
Package 1 Width	0.4 in (1 cm)
Package 1 Length	0.4 in (1 cm)
Package weight(Lbs)	2.2 lb(US) (1 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Circularity Profile	No need of specific recycling operations