

Product data sheet

Specifications

SQUARE D



REVERSING DRUM SWITCHES

2601BG1S4

! Discontinued

Main

Device short name B

Complementary

Depth 4.86 in (123.44 mm)

Device Application Manual reversing control

Device mounting Flush

Electrical Connection Screw clamp terminal

Enclosure type Standard environment enclosure indoor

Height 6.62 in (168.15 mm)

Maximum Horse Power Rating
1.5 hp 115 V AC, 1 phase
5 hp 200/230 V AC, 3 phase
3 hp 230 V AC, 1 phase
7.5 hp 460/575 V AC, 3 phase
5 hp 460/575 V AC, 1 phase

Motor starter type Reversing

Operating Mode Normal

Permissible voltage
600 V AC
250 V DC

Switch actuation
Maintained forward
Momentary reverse

Width 3.26 in (82.80 mm)

Environment

NEMA Degree of Protection NEMA 1

Product Certifications
CSA LR25490 class 3211 05
UL listed file E42243 CCN NLRV

Ordering and shipping details

Category 21116-2601

Discount Schedule CP1

GTIN 00785901152163

Returnability No

Country of origin MX

Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package weight(Lbs)	21.60 oz (612.35 g)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No