


Product data sheet

Specifications



auxiliary blown fuse signalling
contact - TeSys GS - 1st C/O - 4
poles - 630 A

GS1AF64

⚠ Discontinued

Main

Range of Product	TeSys GS 630
Device short name	auxiliary blown fuse contact
Product or Component Type	Auxiliary contact
Product Compatibility	GS 630
Poles description	4P
[Ie] rated operational current	12 A 24 V DC-13 2 A 48 V DC-13 3 A 400 V AC-15 4 A 230 V AC-15 0.4 A 220 V DC-13 0.6 A 110 V DC-13

Complementary

Fuse type	NFC DIN
Fuse size	T3
Contacts type and composition	1 NO/NC
Product Weight	0.2 lb(US) (0.1 kg)

Ordering and shipping details

Category	18402-WORLD SERVICE PARTS(CONTROL ACCESS)
Discount Schedule	CP10
GTIN	3389110563405
Returnability	No

Contractual warranty

Warranty (in months)	18
----------------------	----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

California proposition 65

WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.