

Product data sheet

Specifications



universal plug-in relay - Harmony RUM - 2 C/O - 48 V AC - 10 A - with LED

RUMF2AB2E7

⚠ Discontinued on: Oct 31, 2014

⚠ End-of-service on: Dec 31, 2014

⚠ Discontinued

Main

Range of Product	Harmony Relay
Series name	Universal
Product or Component Type	Plug-in relay
Device short name	RUM
[Uc] control circuit voltage	48 V AC
Contacts type and composition	2 C/O
Status LED	With
Control Type	Lockable test button
[Ithe] conventional enclosed thermal current	10 A -40...131 °F (-40...55 °C)

Complementary

[Uimp] rated impulse withstand voltage	4 kV
minimum switching current	10 mA
Minimum switching voltage	17 V
Minimum switching capacity	170 mW
Electrical durability	100000 cycles resistive
Average coil consumption in VA	2...3 60 Hz
Operating time	20 ms
Rated operational voltage limits	38.4...52.8 V AC
[Ui] rated insulation voltage	250 V IEC 300 V CSA 300 V UL
Maximum switching voltage	250 V AC IEC 250 V DC IEC
Drop-out voltage threshold	$\geq 0.15 U_c$ AC
[Ie] rated operational current	10 A AC-1/DC-1 (NO) conforming to IEC 12 A at 28 V DC-1 conforming to UL 16 A at 277 V AC-1 conforming to UL 5 A AC-1/DC-1 (NC) conforming to IEC
Average resistance	290 Ohm 20 °C +/- 15 %
Maximum switching capacity	2500 VA AC 280 W DC
Mechanical durability	5000000 cycles

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Safety reliability data	B10d = 100000
Operating rate	<= 18000 cycles/hour no-load <= 1200 cycles/hour under load
Utilisation coefficient	20 %
Compatibility code	RUM
Dielectric strength	1500 V AC between contacts 1550 V AC between coil and contact 1550 V AC between poles
Protection category	RT I
Pollution degree	3
Operating position	Any position
Contacts material	AgNi
Shape of pin	Flat
Net Weight	0.185 lb(US) (0.084 kg)

Environment

Ambient air temperature for operation	-40...131 °F (-40...55 °C)
IP degree of protection	IP40 conforming to EN/IEC 60529
Standards	CSA C22.2 No 14 EN/IEC 61810-1 UL 508
Product Certifications	CSA GOST UL
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Vibration resistance	3 gn +/- 1 mm 10...150 Hz)10 cycles in operation EN/IEC 60068-2-27 4 gn +/- 1 mm 10...150 Hz)10 cycles not operating EN/IEC 60068-2-27
Shock resistance	10 gn in operation 10 gnnot operating

Ordering and shipping details

Category	21127-ZELIO ICE CUBE RELAYS
Discount Schedule	CP2
GTIN	00785901547983
Returnability	No
Country of origin	CN

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No