

Product datasheet

Specifications



Programmable contacts M6C,
MasterPact NT drawout, 6 NO/NC
contacts 5A/240VAC, for MicroLogic
P/H only

47484

⚠ Discontinued

Main

Range of product	MasterPact NT
Range	MasterPact
Product or component type	Programmable contact
Device application	Control
Range compatibility	Masterpact MasterPact NT circuit breaker

Complementary

Mounting mode	Drawout
[Ie] rated operational current	1.5 A at 48 V DC 1.8 A at 24 V DC 3 A at 380 V AC 5 A at 240 V AC 0.15 A at 250 V DC 0.4 A at 125 V DC
Minimum load	100 mA at 24 V

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins