

Product data sheet

Specifications



Auxiliary contacts, TeSys GS, 2NC + 2NO, instantaneous, right side mounting, for GS2 with left handle test position

GS1ANT22G

! Discontinued

Main

Range of product	TeSys
Device short name	GS1AN
Product or component type	Auxiliary contact
Contact application	O, I and test position signalling
Contacts type and composition	2 NO + 2 NC
Contact operation	Instantaneous
[I _{th}] conventional free air thermal current	20 A (at 40 °C)
[I _e] rated operational current	1 A at 220 V DC-13 10 A at 230 V AC-15 12 A at 127 V AC-15 4 A at 48 V DC-13 6 A at 440 V AC-15 8 A at 400/415 V AC-15 1.2 A at 110 V DC-13

Complementary

Range compatibility	TeSys TeSys GS fuse-switch disconnecter
Mechanical durability	30000 cycles
Electrical durability	30000 cycles AC-15
switch rated current	315 A 400 A 125 A 250 A 160 A 100 A 60 A 200 A 50 A 63 A
Fuse type	NFC BS DIN
Type of operating handle	External left side
Net weight	0.258 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No