

# Product datasheet

Specifications



## Servo motor BCH18, 1kw, L100, 23bit, OPTO MT

BCH18LH1033CA6C

### Main

Range compatibility	Easy Lexium 18
Device short name	BCH18
Product or component type	Servo motor

### Complementary

Maximum mechanical speed	6000.0 rpm
[Us] rated supply voltage	220 V
Continuous stall current	7.3 A
Continuous stall torque	3.18 N.m, 220 V
Continuous power	1000 W
Peak stall torque	9.54 N.m, 220 V
Nominal output power	1000 W, 220 V
Nominal torque	3.18 N.m, 220 V
Nominal speed	3000 rpm, 220 V
Maximum current Irms	at 1.0 kW, 220 V
Maximum permanent current	22.0 A
Product compatibility	Motion servo drive motion servo motors motor at 1.0 kW, 220 V
Shaft end	Parallel key
Shaft diameter	22.0 mm
Shaft length	45.0 mm
Key width	8.0 mm
Feedback type	23 bits optic multi turn encoder
Holding brake	Without
Mounting support	Asian standard flange
Motor flange size	100 mm
Electrical connection	2 connectors male/female
Number of motor poles	5.0
Rotor inertia	1.43 kg.cm <sup>2</sup>
Stator resistance	0.5 Ohm
Stator inductance	3.73 mH
Maximum radial force Fr	686 N

Maximum axial force Fa	196 N
Length	140 mm
Number of mounting holes	4
Circle diameter of the mounting holes	9 mm
Width	140.0 mm
Height	100.0 mm
Depth	152.2 mm
Net weight	3.6 kg
Encoder type	Optic encoder
Inertia	0.0 kg.cm <sup>2</sup> of brake 1.43 kg.cm <sup>2</sup> of motor

## Environment

IP degree of protection	IP67
-------------------------	------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.5 cm
Package 1 Width	18.2 cm
Package 1 Length	27.8 cm
Package 1 Weight	4.328 kg
Unit Type of Package 2	S04
Number of Units in Package 2	4
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	17.312 kg

## Contractual warranty

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	8 095 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	36 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.6 kg CO2 eq.
Carbon footprint of the installation phase [A5]	1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	8 052 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	5 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Use Better



### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>

### Use Longer



### Lifetime extension

Repair	No
--------	----

### Use Again



### Repack and remanufacture

End of life manual availability	<a href="#">End of Life Information</a>
Take-back	Nej
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins