

Product datasheet

Specifications



10 A 1P 6 kA SQO MCB Trip Type C (5-10In)

SQO110EC6

 **Discontinued on:** 27 May 2019

 **Discontinued**

Main

Range of product	Qwikline II
Product type	Miniature circuit-breaker
Device location in system	Outgoer

Complementary

Poles description	1P
Number of protected poles	1
[In] rated current	10 A
Network type	AC
[Ue] rated operational voltage	230/240 V
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity	6 kA
Cable cross section	1...25 mm ²

Environment

Standards	BS EN 60898
-----------	-------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	140.614 g

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins