

Product datasheet

Specifications



ECOFIT Sepam S20/S40 with
Easergy P3U30, Chinese, 2 RJ45,
75 V DC, 119...230 V AC/DC,
24...48 V

REL52465

! Discontinued

! Discontinued on: Jul 8, 2024 AD

Main

Range of product	Easergy P3
User language	Chinese

Complementary

Range compatibility	Sepam series 20 Sepam series 40
Input type	3 CT + CSH
Physical interface	2 RJ45
Switching voltage	75 V DC
[Ue] rated operational voltage	119...230 V AC/DC
[Us] rated supply voltage	24...48 V

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.0 cm
Package 1 Width	30.0 cm
Package 1 Length	40.0 cm
Package 1 Weight	3.5 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
SCIP Number	7fd15df9-a702-4a28-ad01-afb36a7b785f
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins