

Product datasheet

Specifications



ISFL400A - 185 mm busbar one-pole switchable with screws M12

LV480902

⚠ Discontinued on: 9 Feb 2023

EAN Code: 3606480796081

⚠ Discontinued

Main

Range	FuPacT
Product name	FuPacT ISFL
Device short name	ISFL400
Product or component type	Fuse-switch disconnecter
Device application	Equipment protection, monitoring and control Distribution
Signalling function	Separated fuse monitor
Poles description	3 x 1P switchable
Number of fuse carriers	3
Fuse type	DIN
Fuse size	NH2
Suitability for isolation	Yes conforming to EN/IEC 60947-3
Visible break	Yes
Contact position indicator	Yes
[Ith] conventional free air thermal current	400 A (40 °C) power dissipation per fuse: 34 W
[Ithe] conventional enclosed thermal current	400 A at 40 °C, Power dissipation per fuse: 34 W
Maximum power dissipation per pole	53 W
[Ue] rated operational voltage	690 V AC 50/60 Hz 800 V AC 50/60 Hz AC-20 800 V DC DC-20
[Ui] rated insulation voltage	1000 V AC 50/60 Hz 1000 V DC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	AC-21B: 400 A at 220/240 V AC 50/60 Hz AC-21B: 400 A at 380/415 V AC 50/60 Hz AC-21B: 400 A at 440/480 V AC 50/60 Hz AC-21B: 400 A at 500 V AC 50/60 Hz AC-21B: 400 A at 660/690 V AC 50/60 Hz AC-22B: 400 A at 220/240 V AC 50/60 Hz AC-22B: 400 A at 380/415 V AC 50/60 Hz AC-22B: 400 A at 440/480 V AC 50/60 Hz AC-22B: 400 A at 500 V AC 50/60 Hz AC-23B: 400 A at 220/240 V AC 50/60 Hz AC-23B: 400 A at 380/415 V AC 50/60 Hz

Complementary

[Iq] Breaking capacity with fuses (kA RMS)	120 kA at 415 V (AC) 120 kA at 500 V (AC) 120 kA at 690 V (AC)
[Icw] rated short-time withstand current	15 kA for 1 s
[Icm] Rated short-circuit making capacity	30 kA at 690 V
Rated duty	Uninterrupted
Control type	Fuse carriers handle
Provision for padlocking	3 padlocks
Mounting position	Vertical
Mounting mode	Fixed
Mounting support	Busbars
Mounting location	One above the other
Contact operation	Single-break
Mechanical durability	800 cycles
Electrical durability	AC-21B: 200 cycles 690 V AC 50/60 Hz AC-22B: 200 cycles 500 V AC 50/60 Hz AC-23B: 200 cycles 415 V AC 50/60 Hz
Connections - terminals	Screw connection downstream M12 400 A Direct connection upstream 400 A 185 mm
Tightening torque	32 N.m
Width	100 mm
Height	741 mm
Depth	190 mm
Net weight	5 kg
Standards	EN/IEC 60947-1 EN/IEC 60947-3
Product certifications	CE CCC EAC

Environment

Electrical shock protection class	Class II front face
IP degree of protection	IP20 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Pollution degree	3 conforming to IEC 60947
Ambient air temperature for operation	-20...70 °C
Ambient air temperature for storage	-50...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.4 cm
Package 1 Width	21.6 cm
Package 1 Length	78.7 cm

Package 1 Weight	6.0 kg
Unit Type of Package 2	P12
Number of Units in Package 2	50
Package 2 Height	117.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	312.0 kg

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Free of Substances of Very High Concern above the threshold](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins