


Product data sheet

Specifications



AS-Interface - for Ø 22 emergency stop mounting in enclosure - metal

ASISSLE4

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

Main

Product or component type	Interface for Ø 22 emergency stop mounting in enclosure
Range compatibility	AS-Interface cabling system
Product mounting	In enclosure
Fixing collar material	Metal
Number of contacts	2
AS-Interface	0.B.F.F
Supply	Via AS-Interface

Complementary

Addressing	Using adjustment terminal
[Us] rated supply voltage	24 V DC - 15...15 %
Power consumption in W	1.2 W
Current consumption	45 mA for AS-Interface line
Connections - terminals	AS-Interface line: 1 connector
Product weight	0.06 kg

Environment

Standards	EN/IEC 61496-1 ISO 13849-1 category 4 EN/ISO 12100 EN 1088/ISO 14119 EN/ISO 13850 EN/IEC 60204-1 EN/IEC 60947-5-3 EN 954-1 category 4 EN 574/ISO 13851
Product certifications	CSA UL
IP degree of protection	IP00 conforming to IEC 60529
Ambient air temperature for operation	-10...55 °C
Ambient air temperature for storage	-25...85 °C
Shock resistance	10 gn
vibration resistance	5 gn

Packing Units

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.6 cm
Package 1 Width	5.3 cm
Package 1 Length	7.5 cm
Package 1 Weight	77 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

EU RoHS Directive

[Compliant](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins