

# Product data sheet

Specifications

SQUARE D



## Two Speed Manual Starter - NEMA 1 - Buttons - 3P-Size M0-Red Ind-NO Aux 600VAC

2512MBG1V06P11X1

⚠ Discontinued on: Aug 28, 2025

⚠ Discontinued

### Main

Product	Manual Starter
Type	M
NEMA Size	M-0

### Complementary

Control Unit	Push-button
Pilot Light	Red indicator, 480 V
Horsepower Rating	2 hp 200...230 V AC, 3 phases 3 hp 380...575 V AC, 3 phases
Voltage Rating	600 V AC
Number of Poles	3P
Starter Type	2 speed
Electrical Connection	Screw clamp terminals
Overload Relay Type	Melting alloy
Number of Thermal Units Required	3
Wire Gauge	AWG 14...AWG 8 copper
Auxiliary Contacts	1 NO
Height	8.63 in (219.20 mm)
Width	5 in (127 mm)
Depth	4.13 in (104.90 mm)

### Environment

Certifications	CSA LR60905 class 3211 05 UL listed file E42243 CCN NLRV
NEMA Enclosure Rating	NEMA 1 painted sheet steel

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	8.501 lb(US) (3.856 kg)



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No