

Product datasheet

Specifications



ferrite suppressors for downstream contactor opening

VW3A31451

⚠ Discontinued on: 2 Oct 2023

⚠ Discontinued

Main

Product or component type	Ferrite suppressors for downstream contactor opening
Range compatibility	Altivar 312 Altivar 312 Solar Altivar 12
Product specific application	Output filter
compatibility with variable speed drives	Variable speed drive ATV12H at 0.18 kW, 200...240 V, single phase Variable speed drive ATV312 at 0.18 kW, 200...240 V, single phase
Sale per indivisible quantity	3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.2 cm
Package 1 Width	17.0 cm
Package 1 Length	23.5 cm
Package 1 Weight	292.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	2.79 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No