

Product data sheet

Specifications



ASCO 4800 Load Bank

ASCOLBLV4800

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Resistive load bank

Complementary

Voltage Rating
208 V AC 60 Hz, 3 phase
240/480 V AC 60 Hz, 3 phase
240 V AC 60 Hz, 3 phase
400 V AC 50 Hz, 3 phase
480 V AC 60 Hz, 3 phase
600 V AC 60 Hz, 3 phase

Capacity Rating
450 kW
500 kW
600 kW
750 kW
1000 kW
1250 kW
1500 kW
1750 kW
2000 kW
2500 kW
3000 kW

Load Step Resolution
5 kW
50 kW

Cooling System Rating
8976779.9 Gal/hr(US) (33980.2 m3/h)

Provided Equipment
Switch 3 On-Off
LED 2 on
LED 1 alarm indication
Fuse
Cooling fans

Enclosure Material
Aluminium
Steel

Surface Finish
Polyester powder

Color
Gray

Connection Terminals
Terminals inside)

Length
59.02 in (1499 mm)

Width
120 in (3048 mm)

Height
156.0 in (3962 mm)

Product Weight
5500.5 lb(US) (2495 kg)

Environment

Ambient Air Temperature
-18...122 °F (-28...50 °C)

Standards
ISO 9001
NEMA

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Contractual warranty

Warranty (in months)

18



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	No
--------------------------------------	----

Use Longer



Lifetime extension

Repair	No
--------	----