

# Product data sheet

Specifications



## Circuit breaker, Stab-Lok, 100A, 3 pole, 240VAC, 10kA, bolt on mount

NB3P100

### Main

Range of product	Stab-lok
Product or component type	Miniature circuit-breaker

### Complementary

[In] rated current	100 A
[Ue] rated operational voltage	120/240 V AC
Mounting mode	Bolt-on
Poles description	3P
Breaking capacity	10 kA
Electrical connection	Screw connector
AWG gauge	AWG 14...AWG 1/0 aluminum/copper

### Environment

Product certifications	CSA
------------------------	-----

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.00 in (7.62 cm)
Package 1 Width	3.200 in (8.128 cm)
Package 1 Length	4.50 in (11.43 cm)
Package 1 Weight	20.960 oz (594.206 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	6
Package 2 Height	3.700 in (9.398 cm)
Package 2 Width	9.400 in (23.876 cm)
Package 2 Length	9.800 in (24.892 cm)
Package 2 Weight	8.236 lb(US) (3.736 kg)

### Contractual warranty

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

SCIP Number

770cc9ea-53d2-4d3d-a57a-062b35abd847

EU RoHS Directive

[Compliant By Exemption](#)

REACH Regulation

[Reference contains Substances of Very High Concern above the threshold](#)

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture

Circularity Profile

No need of specific recycling operations

Take-back

No