

Product data sheet

Specifications



ASCO 7700 Load Bank

ASCOLBLV7700

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Resistive load bank

Complementary

Capacity Rating 937.5...3125 kVA

Load Step Resolution 5 kW
3.75 kvar

Voltage Rating 480 V AC 60 Hz, 3 phase
600 V AC 60 Hz, 3 phase

Resistor Load Tolerance 5 %

Cooling System Rating 8976779.9 Gal/hr(US) (33980.2 m3/h)

Ambient Air Temperature -18...122 °F (-28...50 °C)

Provided Equipment Switch 3 On-Off
LED 2 on
LED 1 alarm indication
Voltage transformer 1 inside the enclosure
Cooling fans inside the enclosure

Connection Terminals 1 connector connection box)

Enclosure Material Aluminium
Steel

Color Gray

Width 76.0 in (1930 mm)

Height 114.02 in (2896 mm)

Environmental

Standards NEMA
ISO 9001

Contractual warranty

Warranty (in months) 18

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

Use Longer



Lifetime extension

Repair **No**