

AS-Interface Control cabinet module VA module A/B slave, IP20, 4 DI/3 DO Input current: up to 30 mA Output current: 2 A

### Mechanical data

shock resistance 15 g / 11 ms

### Certificates/ approvals

General Product Approval

EMV

Maritime application



other

Environment

Industrial Communication

[Miscellaneous](#)

[Confirmation](#)



[Environmental Con-  
firmations](#)



### Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK2400-1FG01-0AA1>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK2400-1FG01-0AA1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK2400-1FG01-0AA1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RK2400-1FG01-0AA1&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK2400-1FG01-0AA1&lang=en)

last modified:

4/4/2026