

Product datasheet

Specifications



AC servo motor BSH - 2.8 N.m - 1500 rpm - untapped shaft - without brake - IP50

BSH0703M01A1A

⚠ Discontinued on: 18 Apr 2024

⚠ To be end-of-service on: 18 Apr 2026

⚠ Discontinued

Main

Device short name	BSH
Product or component type	Servo motor
Maximum mechanical speed	8000 rpm
Continuous stall torque	2.8 N.m for LXM05AD10M2, 200...240 V, single phase 2.8 N.m for LXM05BD10M2, 200...240 V, single phase 2.8 N.m for LXM05CD10M2, 200...240 V, single phase 2.8 N.m for LXM05AD10M3X, 200...240 V, three phase 2.8 N.m for LXM05AD14N4, 380...480 V, three phase 2.8 N.m for LXM05BD10M3X, 200...240 V, three phase 2.8 N.m for LXM05BD14N4, 380...480 V, three phase 2.8 N.m for LXM05CD10M3X, 200...240 V, three phase 2.8 N.m for LXM05CD14N4, 380...480 V, three phase
Peak stall torque	8.6 N.m for LXM05AD10M2, 200...240 V, single phase 8.6 N.m for LXM05BD10M2, 200...240 V, single phase 8.6 N.m for LXM05CD10M2, 200...240 V, single phase 8.6 N.m for LXM05AD10M3X, 200...240 V, three phase 8.6 N.m for LXM05AD14N4, 380...480 V, three phase 8.6 N.m for LXM05BD10M3X, 200...240 V, three phase 8.6 N.m for LXM05BD14N4, 380...480 V, three phase 8.6 N.m for LXM05CD10M3X, 200...240 V, three phase 8.6 N.m for LXM05CD14N4, 380...480 V, three phase
Nominal output power	400 W for LXM05AD10M2, 200...240 V, single phase 400 W for LXM05BD10M2, 200...240 V, single phase 400 W for LXM05CD10M2, 200...240 V, single phase 400 W for LXM05AD10M3X, 200...240 V, three phase 400 W for LXM05BD10M3X, 200...240 V, three phase 400 W for LXM05CD10M3X, 200...240 V, three phase 750 W for LXM05AD14N4, 380...480 V, three phase 750 W for LXM05BD14N4, 380...480 V, three phase 750 W for LXM05CD14N4, 380...480 V, three phase
Nominal torque	2.63 N.m for LXM05AD10M2, 200...240 V, single phase 2.63 N.m for LXM05BD10M2, 200...240 V, single phase 2.63 N.m for LXM05CD10M2, 200...240 V, single phase 2.4 N.m for LXM05AD14N4, 380...480 V, three phase 2.4 N.m for LXM05BD14N4, 380...480 V, three phase 2.4 N.m for LXM05CD14N4, 380...480 V, three phase 2.63 N.m for LXM05AD10M3X, 200...240 V, three phase 2.63 N.m for LXM05BD10M3X, 200...240 V, three phase 2.63 N.m for LXM05CD10M3X, 200...240 V, three phase
Nominal speed	1500 rpm for LXM05AD10M2, 200...240 V, single phase 1500 rpm for LXM05BD10M2, 200...240 V, single phase 1500 rpm for LXM05CD10M2, 200...240 V, single phase 1500 rpm for LXM05AD10M3X, 200...240 V, three phase 1500 rpm for LXM05BD10M3X, 200...240 V, three phase 1500 rpm for LXM05CD10M3X, 200...240 V, three phase 3000 rpm for LXM05AD14N4, 380...480 V, three phase 3000 rpm for LXM05BD14N4, 380...480 V, three phase 3000 rpm for LXM05CD14N4, 380...480 V, three phase

Product compatibility	LXM05AD10M2 at 200...240 V single phase LXM05BD10M2 at 200...240 V single phase LXM05CD10M2 at 200...240 V single phase LXM05AD10M3X at 200...240 V three phase LXM05BD10M3X at 200...240 V three phase LXM05CD10M3X at 200...240 V three phase LXM05AD14N4 at 380...480 V three phase LXM05BD14N4 at 380...480 V three phase LXM05CD14N4 at 380...480 V three phase
Shaft end	Untapped
IP degree of protection	IP50 standard
Speed feedback resolution	131072 points/turn
Holding brake	Without
Mounting support	International standard flange
Electrical connection	Straight connectors

Complementary

Range compatibility	Lexium 05
supply voltage max	480 V
Network number of phases	Three phase
Continuous stall current	2.1 A
maximum continuous power	1.7 W
Maximum current Irms	8.7 A for LXM05AD10M2 8.7 A for LXM05AD10M3X 8.7 A for LXM05AD14N4 8.7 A for LXM05BD10M2 8.7 A for LXM05BD10M3X 8.7 A for LXM05BD14N4 8.7 A for LXM05CD10M2 8.7 A for LXM05CD10M3X 8.7 A for LXM05CD14N4
Maximum permanent current	8.7 A
Switching frequency	4 kHz
Second shaft	Without second shaft end
Shaft diameter	14 mm
Shaft length	30 mm
Feedback type	Single turn SinCos Hiperface
Motor flange size	70 mm
Torque constant	1.48 N.m/A at 120 °C
Back emf constant	95 V/krpm at 120 °C
Number of motor poles	6
Rotor inertia	0.58 kg.cm ²
Stator resistance	10.2 Ohm at 20 °C
Stator inductance	49.2 mH at 20 °C
Stator electrical time constant	4.82 ms at 20 °C
Maximum radial force Fr	400 N at 6000 rpm 430 N at 5000 rpm 460 N at 4000 rpm 510 N at 3000 rpm 580 N at 2000 rpm 730 N at 1000 rpm

Maximum axial force Fa	0.2 x Fr
Type of cooling	Natural convection
Length	220 mm
Centring collar diameter	60 mm
Centring collar depth	2.5 mm
Number of mounting holes	4
Mounting holes diameter	5.5 mm
Circle diameter of the mounting holes	82 mm
Net weight	3.62 kg
Sizing reference	BSH0703M
Network number of phases	3
Accuracy error [angular]	1.4 °
Temperature copper hot	120 °C
Temperature magnet hot	100 °C
Temperature magnet rt	20 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.3 cm
Package 1 Width	12.8 cm
Package 1 Length	37.7 cm
Package 1 Weight	3.6 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

SCIP Number	8c11b0c9-e501-4810-83eb-05fc6605ede4
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
PVC free	Yes

Use Longer




Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

End of life manual availability	No need of specific recycling operations
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins