



SIMATIC S7-200 SMART CPU CR20s, COMPACT CPU, AC/DC/RELAY,  
ONBOARD I/O: 12 DI 24V DC; 8 DO RELAY 2A; POWER SUPPLY: AC, 85 - 264  
V AC AT 47 - 63 HZ, PROGRAM/DATA MEMORY: 20 KB

General information	
Product type designation	CPU CR20 AC/DC/relay
Engineering with	
<ul style="list-style-type: none"> <li>Programming package</li> </ul>	STEP 7 Micro/WIN SMART
Installation type/mounting	
Rail mounting	Yes; Standard - DIN rail
Supply voltage	
Rated value (AC)	230 V; 230 V AC (L1, N)
<ul style="list-style-type: none"> <li>120 V AC</li> </ul>	Yes; 85 to 132 V AC
<ul style="list-style-type: none"> <li>230 V AC</li> </ul>	Yes; 170 to 264 V AC
permissible range, lower limit (AC)	85 V
permissible range, upper limit (AC)	264 V
Reverse polarity protection	No
Line frequency	
<ul style="list-style-type: none"> <li>permissible range, lower limit</li> </ul>	47 Hz
<ul style="list-style-type: none"> <li>permissible range, upper limit</li> </ul>	63 Hz
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>permissible range, lower limit (DC)</li> </ul>	5 V
<ul style="list-style-type: none"> <li>permissible range, upper limit (DC)</li> </ul>	250 V
Input current	
Current consumption (rated value)	60 mA; At 220 V AC
Current consumption, max.	80 mA; At 220 V AC
Inrush current, max.	16.3 A; at 264 V
Power loss	
Power loss, max.	6 W
Storage	
Type of memory	DDR
Flash	Yes
RAM	Yes
Micro Memory Card	No
CPU processing times	
for bit operations, typ.	150 ns; / instruction
for word operations, typ.	1.2 µs; / instruction
for floating point arithmetic, typ.	3.6 µs; / instruction
Hardware configuration	
Integrated power supply	No
Time of day	
Clock	

• Type	Software clock
• Hardware clock (real-time)	No
<b>Digital inputs</b>	
Number of digital inputs	12; Integrated
• of which inputs usable for technological functions	4; HSC: 4 @ 100 kHz single phase, 2 @ 50 kHz A/B phase
Sourcing/sinking input	Yes
<b>Input voltage</b>	
• Type of input voltage	DC
• Rated value (DC)	24 V; DC at 4 mA nominal
• for signal "0"	< 5 V DC
• for signal "1"	+15 to +30 V
<b>Input current</b>	
• for signal "0", max. (permissible quiescent current)	1 mA
• for signal "1", typ.	4 mA
<b>Input delay (for rated value of input voltage)</b>	
for standard inputs	
— parameterizable	Yes; 0.2 $\mu$ s, 0.4 $\mu$ s, 0.8 $\mu$ s, 1.6 $\mu$ s, 3.2 $\mu$ s, 6.4 $\mu$ s and 12.8 $\mu$ s, selectable in 4 groups
— at "0" to "1", min.	0.2 $\mu$ s
— at "0" to "1", max.	12.8 $\mu$ s
for interrupt inputs	
— Parameterizable	Yes
<b>Cable length</b>	
• shielded, max.	500 m; Standard input: 500 m, high-speed counters: 50 m
• unshielded, max.	300 m
<b>Digital outputs</b>	
Number of digital outputs	8; Relays
<b>Switching capacity of the outputs</b>	
• with resistive load, max.	2 A
• on lamp load, max.	30 W; 30 W with DC, 200 W with AC
<b>Output delay with resistive load</b>	
• "0" to "1", max.	10 ms; max.
• "1" to "0", max.	10 ms; max.
<b>Switching frequency</b>	
• of the pulse outputs, with resistive load, max.	1 Hz
<b>Relay outputs</b>	
• Number of relay outputs	8
• Number of operating cycles, max.	10 000 000; mechanically 10 million, at rated load voltage 100 000
<b>Cable length</b>	
• shielded, max.	500 m
• unshielded, max.	300 m
<b>Interfaces</b>	
Number of industrial Ethernet interfaces	0
Number of RS 485 interfaces	1
Optical interface	No
<b>1. Interface</b>	
Interface type	RS 485 (max. 187.5 kbps)
Isolated	Yes; 500 V AC or 707 V DC
<b>Interface types</b>	
• RS 485	Yes
• Design of the connection	9-pin sub D socket
<b>Protocols</b>	
Supports protocol for PROFINET IO	No
PROFIBUS	No
<b>Protocols (Ethernet)</b>	
• TCP/IP	No
<b>EMC</b>	
<b>Interference immunity against discharge of static electricity</b>	
• Interference immunity against discharge of static	Yes

electricity acc. to IEC 61000-4-2	
— Test voltage at air discharge	8 kV
— Test voltage at contact discharge	4 kV
<b>Interference immunity against high-frequency electromagnetic fields</b>	
• Interference immunity against high-frequency radiation acc. to IEC 61000-4-3	Yes; 10 V/m, 80 to 1 000 MHz (to IEC 61000-4-3); 10 V/m, 900 MHz, 1.89 GHz, 50% ED (to IEC 61000-4-3)
— Frequency range of the RF radiation	10 V/m for 80 MHz ~ 1 GHz, 3 V/m for 1.4 GHz ~ 2 GHz, 3 V/m for 87 MHz ~ 108 MHz, 174 MHz ~ 230 MHz, 470 MHz ~ 790 MHz, 1.4 GHz ~ 2 GHz, 1 V/m for 2 GHz ~ 2.7 GHz
<b>Interference immunity to cable-borne interference</b>	
• Interference immunity on supply lines acc. to IEC 61000-4-4	Yes; ±2 kV acc. to IEC 61000-4-4, burst; surge measurements with additional protective elements
• Interference immunity on signal cables acc. to IEC 61000-4-4	Yes; ±2 kV acc. to IEC 61000-4-4, Burst
<b>Interference immunity against voltage surge</b>	
• Interference immunity on supply lines acc. to IEC 61000-4-5	Yes; ±1 kV (acc. to IEC 61000-4-5; 1995; surge symm.), ±2 kV (acc. to IEC 61000-4-5; 1995; surge asymm.), no external protective circuit required
• asymmetric interference	
— Test voltage on supply cables	2 kV
— Test voltage on signal cables >30m	2 kV
<b>Interference immunity against conducted variable disturbance induced by high-frequency fields</b>	
• Interference immunity against high frequency current feed acc. to IEC 61000-4-6	Yes; 10 V, 150 kHz to 80 MHz (to IEC 61000-4-6)
<b>Emission of radio interference acc. to EN 55 011</b>	
• Limit class A, for use in industrial areas	Yes; Emission of radio interference acc. to EN 61000-6-4 +A1 for use in industrial environments
<b>Emission of conducted and non-conducted interference</b>	
• Interference emission via line/AC current cables	EN 61000-6-4, interference emission: Intended for use in industrial areas.
<b>Degree and class of protection</b>	
IP degree of protection	IP20
<b>Standards, approvals, certificates</b>	
CE mark	Yes
<b>Ambient conditions</b>	
<b>Free fall</b>	
• Fall height, max.	0.5 m; five times, in product package
<b>Ambient temperature during operation</b>	
• min.	0 °C
• max.	55 °C
• horizontal installation, min.	0 °C
• horizontal installation, max.	55 °C
• vertical installation, min.	0 °C
• vertical installation, max.	45 °C
<b>Ambient temperature during storage/transportation</b>	
• min.	-40 °C
• max.	70 °C
<b>Air pressure acc. to IEC 60068-2-13</b>	
• Storage/transport, min.	660 hPa
• Storage/transport, max.	1 080 hPa
<b>Altitude during operation relating to sea level</b>	
• Installation altitude, min.	-1 000 m
• Installation altitude, max.	2 000 m
<b>Relative humidity</b>	
• Operation at 25 °C without condensation, max.	95 %
<b>Configuration</b>	
<b>Programming</b>	
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
<b>Dimensions</b>	
Width	90 mm

Height	100 mm
Depth	81 mm
<b>Weights</b>	
Weight, approx.	365 g; approx.
<b>Classifications</b>	

	Version	Classification
eClass	14	27-24-22-07
eClass	12	27-24-22-07
eClass	9.1	27-24-22-07
eClass	9	27-24-22-07
eClass	8	27-24-22-07
eClass	7.1	27-24-22-07
eClass	6	27-24-22-07
ETIM	10	EC000236
ETIM	9	EC000236
ETIM	8	EC000236
ETIM	7	EC000236
IDEA	4	3565
UNSPSC	15	32-15-17-05

**Approvals / Certificates**

**General Product Approval**



[China RoHS](#)

last modified:

8/24/2025