

Product datasheet

Specifications



OneMotorCable SH3 motor to Lexium 62 drive, 1,5MM2, M17, UL, 25m

VW3ED132R250

EAN Code: 3606489916237

Main

Range of product	PacDrive 3
Product or component type	Hybrid cable

Complementary

Range compatibility	Lexium 62
Product compatibility	LXM 62 servo drive SH3040 servo motor SH3055 servo motor
Type of cable	Shielded cable
Connector type	1 x M17 quicklock, round shape 1 x RJ45
Material	Metal
Accessory / separate part destination	Holding brake Hiperface DSL shielded
Cable length	25 m
Product weight	5.27 kg
Accessory / separate part category	Connection accessories

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.000 cm
Package 1 Width	42.000 cm
Package 1 Length	42.000 cm
Package 1 Weight	5.300 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	42 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	31 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.7 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	10 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	21
End of life manual availability	End of Life Information
Take-back	No