


Product datasheet

Specifications



passive filter, Altivar, 370A, 400V,
for variable speed drive

VW3A4633

⚠ Discontinued on: 5 Aug 2021

⚠ End-of-service on: 24 Nov 2021

⚠ Discontinued

Main

Product or component type	Passive filter
Product specific application	Reduction of current harmonics

Complementary

Range compatibility	Altivar 71 Altivar 61
[Us] rated supply voltage	400 V +/- 10 %
power supply frequency	50 Hz +/- 5 %
Quantity per drive	1 filter per drive for ATV61HC22N4 1 filter per drive for ATV71HC20N4 1 filter per drive for ATV71HC25N4 3 filters per drive for ATV61HC63N4
[In] rated current	370 A
Network number of phases	3 phases
THDI	5 % for ATV71HC25N4 ATV71H motor: 250 kW/400 hp 5 % for ATV61HC22N4 ATV61H motor: 220 kW/350 hp 5 % for ATV61HC63N4 ATV61H motor: 560 kW/800 hp 5 % for ATV71HC20N4 ATV71H motor: 200 kW/300 hp
Max current	1.5 x nominal current
Efficiency	98 %
Cos phi	1 (150 % of line current) 0.85 (75 % of line current) 0.99 (100 % of line current)
Electrical connection	bare wires diameter: 16.5 mm
Electrical insulation class	Class F
Net weight	320 kg

Environment

IP degree of protection	IP20
Relative humidity	5...85 % without condensation
Ambient air temperature for operation	40...55 °C (with current derating 3 % per °C) 5...40 °C (without current derating)
Ambient air temperature for storage	-25...55 °C
Operating altitude	<= 1000 m without current derating > 1000...4000 m with current derating 5 % per 1000 m

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)


[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Dimensions Drawings

Dimensions



Mounting and Clearance

Mounting Recommendations

Horizontal or Vertical Mounting

