

Product data sheet

Specifications



extra neutral bar for distribution terminal block - 125 A

13517

⚠ Discontinued on: 11 Oct 2019

⚠ Discontinued

Main

Range of product	Canalis KV Prisma G Prisma PH Prisma P Prisma GX
Product or component type	Extension module
Comb busbar, distribution terminal block accessory type	Neutral bar
Poles description	1N
Accessory / separate part category	Connection accessories

Complementary

Distribution block outgoers	4 x 13 holes
Mounting support	35 mm symmetrical DIN rail Multifix rail
[Ie] rated operational current	125 A
[Ui] rated insulation voltage	500 V AC
[Icw] rated short-time withstand current	3.5 kA for 1 s
[Ipk] rated peak withstand current	20 kA
Busbar length	107 mm
Kit composition	Insulating back Cover Open screws
Connections - terminals	Cable 6...16 mm ² semi-rigid
Product compatibility	Pragma D18 modular enclosures Pragma C12 modular enclosures All enclosures Pragma F24 modular enclosures Prisma functional enclosures

Environment

Standards	EN 60947-7-1
Pollution degree	3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)

18



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

End of life manual availability

No need of specific recycling operations

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins