

# Product datasheet

Specifications



## NG125 - circuit breaker - NG125L - 2P - 80A - C curve

18796

### Main

Range	Acti9
Product name	Acti9 NG125
Product or component type	Miniature circuit-breaker
Device short name	NG125L
Device application	Distribution
Poles description	2P
Number of protected poles	2
Neutral position	Left
[In] rated current	80 A at 40 °C
Network type	DC AC
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity	100 kA Icu at 220...240 V AC 50/60 Hz conforming to EN/IEC 60947-2 40 kA Icu at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2 50 kA Icu at 380...415 V AC 50/60 Hz conforming to EN/IEC 60947-2 15 kA Icu at 500 V AC 50/60 Hz conforming to EN/IEC 60947-2 36 kA Icu at <= 250 V DC conforming to EN/IEC 60947-2
Utilisation category	Category A conforming to IEC 60947-2
Suitability for isolation	Yes conforming to IEC 60947-2
Standards	EN/IEC 60947-2

### Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	380...415 V AC 50/60 Hz 500 V AC 50/60 Hz 220...240 V AC 50/60 Hz 440 V AC 50/60 Hz <= 250 V DC
Magnetic tripping limit	8 x In +/- 20 %
[Ics] rated service breaking capacity	75 kA 75 % conforming to EN/IEC 60947-2 - 220...240 V AC 50/60 Hz 37.5 kA 75 % conforming to EN/IEC 60947-2 - 380...415 V AC 50/60 Hz 30 kA 75 % conforming to EN/IEC 60947-2 - 440 V AC 50/60 Hz 11.25 kA 75 % conforming to EN/IEC 60947-2 - 500 V AC 50/60 Hz 50 kA 100 % conforming to EN/IEC 60947-2 - 250 V DC
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to EN/IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 60947-2
Contact position indicator	Yes

Excluding VAT, FCA Jabal Ali & amp; are subject to change – check with your local distributor.

<b>Control type</b>	Toggle Manual tripping test
<b>Local signalling</b>	ON/OFF indication Trip indicator
<b>Mounting mode</b>	Clip-on
<b>Mounting position</b>	Vertical
<b>Mounting support</b>	35 mm symmetrical DIN rail
<b>Comb busbar and distribution block compatibility</b>	NO
<b>9 mm pitches</b>	6
<b>Height</b>	103 mm
<b>Depth</b>	81 mm
<b>Width</b>	54 mm
<b>Net weight</b>	0.48 kg
<b>Mechanical durability</b>	20000 cycles
<b>Electrical durability</b>	5000 cycles
<b>Provision for padlocking</b>	Padlockable
<b>Locking options description</b>	Integrated padlocking
<b>Connections - terminals</b>	Tunnel type terminals16...70 mm <sup>2</sup> rigid Tunnel type terminals10...50 mm <sup>2</sup> flexible
<b>Wire stripping length</b>	20 mm
<b>Tightening torque</b>	6 N.m
<b>Earth-leakage protection</b>	Separate block

## Environment

<b>IP degree of protection</b>	IP20 conforming to IEC 60529
<b>IK degree of protection</b>	IK05 conforming to EN/IEC 62262
<b>Pollution degree</b>	3 conforming to IEC 60947-2
<b>Overvoltage category</b>	IV
<b>Tropicalisation</b>	2 conforming to IEC 60068-1
<b>Relative humidity</b>	95 % at 55 °C
<b>Operating altitude</b>	2000 m
<b>Ambient air temperature for operation</b>	-30...70 °C
<b>Ambient air temperature for storage</b>	-40...70 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	5.8 cm
<b>Package 1 Width</b>	8.6 cm
<b>Package 1 Length</b>	11.1 cm
<b>Package 1 Weight</b>	502 g
<b>Unit Type of Package 2</b>	BB1

<b>Number of Units in Package 2</b>	6
<b>Package 2 Height</b>	9.3 cm
<b>Package 2 Width</b>	11.9 cm
<b>Package 2 Length</b>	36 cm
<b>Package 2 Weight</b>	3.099 kg
<b>Unit Type of Package 3</b>	S03
<b>Number of Units in Package 3</b>	36
<b>Package 3 Height</b>	30 cm
<b>Package 3 Width</b>	30 cm
<b>Package 3 Length</b>	40 cm
<b>Package 3 Weight</b>	19.081 kg

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	64 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	3 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	59 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
SCIP Number	282497db-b1ca-4c71-962c-f8cda8e058bf
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>
Halogen-free status	Product contains halogen above thresholds

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	58
End of life manual availability	No need of specific recycling operations
Take-back	Nej
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins