


Product datasheet

Specifications



voltage release Compact MN - 220..240 V DC/AC 50/60Hz

44926

⚠ Discontinued on: 23 Jan 2021

⚠ Discontinued

Main

Range	ComPact
Range of product	C1251
Device short name	MN
Product or component type	Voltage release
Device application	Control
Voltage release type	Undervoltage release
[Uc] control circuit voltage	250 V DC
Range compatibility	ComPact Compact C

Complementary

Operating threshold	0.35...0.7 Un opening 0.85 Un closing
Supply holding power	< 5 W
Auxiliary connection terminal	Screw terminal 0...1.5 mm²

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins