

Product datasheet

Specifications



on mounting plate DOL starter - TeSys LC4-D - 9 A - coil 220 V AC

LC4D09AM7

! Discontinued

Main

Range of product	TeSys
Device short name	LC4
Product or component type	DOL starter
Motor power kW	4 kW at 380...400 V AC 50/60 Hz 4 kW at 415 V AC 50/60 Hz 4 kW at 440 V AC 50/60 Hz 2.2 kW at 220...230 V AC 50/60 Hz 5.5 kW at 500 V AC 50/60 Hz
Utilisation category	AC-3
[Ue] rated operational voltage	220 V AC 50/60 Hz
[Ie] rated operational current	9 A

Complementary

Device composition	Contacteur Fuse disconnecteur
Mounting support	Plate
Width	86 mm
Height	173 mm
Depth	98 mm
Net weight	0.87 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.5 cm
Package 1 Width	10.5 cm
Package 1 Length	11 cm
Package 1 Weight	870 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

EU RoHS Directive

[Compliant](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins