



Load feeder fuseless, Reversing duty 400 V AC, Size S00 0.55...0.80 A 230 V AC  
Spring-type terminal for 60 mm busbar systems (also fulfills type of coordination 1)  
Type of coordination 2, I<sub>q</sub> = 150 kA 1 NC (contactor)

|                                                                                     |                               |
|-------------------------------------------------------------------------------------|-------------------------------|
| product brand name                                                                  | SIRIUS                        |
| product designation                                                                 | Reversing starter             |
| design of the product                                                               | for 60 mm busbars             |
| product type designation                                                            | 3RA22                         |
| manufacturer's article number                                                       |                               |
| • of the supplied contactor                                                         | <a href="#">3RT2015-2AP02</a> |
| • of the supplied circuit-breakers                                                  | <a href="#">3RV2011-0HA20</a> |
| • of the supplied RS assembly kit                                                   | <a href="#">3RA2913-1DB2</a>  |
| • of the supplied link module                                                       | <a href="#">3RA2911-2AA00</a> |
| <b>General technical data</b>                                                       |                               |
| size of the circuit-breaker                                                         | S00                           |
| size of load feeder                                                                 | S00                           |
| power loss [W] for rated value of the current                                       |                               |
| • at AC in hot operating state per pole                                             | 2.6 W                         |
| • without load current share typical                                                | 4.2 W                         |
| type of calculation of power loss current-dependent                                 | quadratic                     |
| insulation voltage with degree of pollution 3 at AC rated value                     | 690 V                         |
| surge voltage resistance rated value                                                | 6 kV                          |
| degree of protection NEMA rating                                                    | other                         |
| shock resistance according to IEC 60068-2-27                                        | 6 g / 11 ms                   |
| mechanical service life (operating cycles) of contactor typical                     | 30 000 000                    |
| type of coordination                                                                | 2                             |
| reference code according to IEC 81346-2:2019                                        | Q                             |
| Substance Prohibitance (day/month/year)                                             | 10/01/2009                    |
| SVHC substance name                                                                 | Lead CAS-No. 7439-92-1        |
| Net Weight                                                                          | 1.79 kg                       |
| <b>Ambient conditions</b>                                                           |                               |
| ambient temperature                                                                 |                               |
| • during operation                                                                  | -20 ... +60 °C                |
| • during storage                                                                    | -50 ... +80 °C                |
| • during transport                                                                  | -50 ... +80 °C                |
| temperature compensation                                                            | -20 ... +60 °C                |
| relative humidity during operation                                                  | 10 ... 95 %                   |
| <b>Main circuit</b>                                                                 |                               |
| number of poles for main current circuit                                            | 3                             |
| design of the switching contact                                                     | electromechanical             |
| adjustable current response value current of the current-dependent overload release | 0.55 ... 0.8 A                |
| operating voltage                                                                   |                               |

|                                                                                                                                                        |                                        |
|--------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| <ul style="list-style-type: none"> <li>• rated value</li> </ul>                                                                                        | 690 V                                  |
| <ul style="list-style-type: none"> <li>• at AC-3 rated value maximum</li> </ul>                                                                        | 690 V                                  |
| <ul style="list-style-type: none"> <li>• at AC-3e rated value maximum</li> </ul>                                                                       | 690 V                                  |
| <b>operating frequency rated value</b>                                                                                                                 | 50 ... 60 Hz                           |
| <b>operational current</b>                                                                                                                             |                                        |
| <ul style="list-style-type: none"> <li>• at AC-3 at 400 V rated value</li> </ul>                                                                       | 0.8 A                                  |
| <ul style="list-style-type: none"> <li>• at AC-3e at 400 V rated value</li> </ul>                                                                      | 0.8 A                                  |
| <b>operating power</b>                                                                                                                                 |                                        |
| <ul style="list-style-type: none"> <li>• at AC-3 <ul style="list-style-type: none"> <li>— at 400 V rated value</li> </ul> </li> </ul>                  | 180 W                                  |
| <ul style="list-style-type: none"> <li>• at AC-3e <ul style="list-style-type: none"> <li>— at 400 V rated value</li> </ul> </li> </ul>                 | 180 W                                  |
| <b>Control circuit/ Control</b>                                                                                                                        |                                        |
| <b>type of voltage of the control supply voltage</b>                                                                                                   | AC                                     |
| <b>control supply voltage at AC</b>                                                                                                                    |                                        |
| <ul style="list-style-type: none"> <li>• at 50 Hz rated value</li> </ul>                                                                               | 230 V                                  |
| <ul style="list-style-type: none"> <li>• at 60 Hz rated value</li> </ul>                                                                               | 230 V                                  |
| <b>apparent holding power of magnet coil at AC</b>                                                                                                     | 4.2 VA                                 |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                                                                                           | 4.2 VA                                 |
| <ul style="list-style-type: none"> <li>• at 60 Hz</li> </ul>                                                                                           | 3.3 VA                                 |
| <b>inductive power factor with the holding power of the coil</b>                                                                                       | 0.25                                   |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                                                                                           | 0.25                                   |
| <ul style="list-style-type: none"> <li>• at 60 Hz</li> </ul>                                                                                           | 0.25                                   |
| <b>Auxiliary circuit</b>                                                                                                                               |                                        |
| <b>product extension auxiliary switch</b>                                                                                                              | Yes                                    |
| <b>Protective and monitoring functions</b>                                                                                                             |                                        |
| <b>trip class</b>                                                                                                                                      | CLASS 10                               |
| <b>design of the overload release</b>                                                                                                                  | thermal (bimetallic)                   |
| response value current of instantaneous short-circuit trip unit                                                                                        | 10 A                                   |
| <b>UL/CSA ratings</b>                                                                                                                                  |                                        |
| <b>full-load current (FLA) for 3-phase AC motor</b>                                                                                                    |                                        |
| <ul style="list-style-type: none"> <li>• at 480 V rated value</li> </ul>                                                                               | 0.8 A                                  |
| <ul style="list-style-type: none"> <li>• at 600 V rated value</li> </ul>                                                                               | 0.8 A                                  |
| <b>yielded mechanical performance [hp]</b>                                                                                                             |                                        |
| <ul style="list-style-type: none"> <li>• for 3-phase AC motor <ul style="list-style-type: none"> <li>— at 460/480 V rated value</li> </ul> </li> </ul> | 0.5 hp                                 |
| <ul style="list-style-type: none"> <li>— at 575/600 V rated value</li> </ul>                                                                           | 0.5 hp                                 |
| <b>Short-circuit protection</b>                                                                                                                        |                                        |
| <b>product function short circuit protection</b>                                                                                                       | Yes                                    |
| <b>design of the short-circuit trip</b>                                                                                                                | magnetic                               |
| <b>conditional short-circuit current (I<sub>q</sub>)</b>                                                                                               |                                        |
| <ul style="list-style-type: none"> <li>• at 400 V according to IEC 60947-4-1 rated value</li> </ul>                                                    | 150 000 A                              |
| <b>Installation/ mounting/ dimensions</b>                                                                                                              |                                        |
| <b>mounting position</b>                                                                                                                               | vertical                               |
| <b>fastening method</b>                                                                                                                                | for snapping onto 60 mm busbar systems |
| <b>height</b>                                                                                                                                          | 260 mm                                 |
| <b>width</b>                                                                                                                                           | 90 mm                                  |
| <b>depth</b>                                                                                                                                           | 155 mm                                 |
| <b>required spacing</b>                                                                                                                                |                                        |
| <ul style="list-style-type: none"> <li>• for grounded parts <ul style="list-style-type: none"> <li>— forwards</li> </ul> </li> </ul>                   | 32 mm                                  |
| <ul style="list-style-type: none"> <li>— backwards</li> </ul>                                                                                          | 0 mm                                   |
| <ul style="list-style-type: none"> <li>— upwards</li> </ul>                                                                                            | 50 mm                                  |
| <ul style="list-style-type: none"> <li>— at the side</li> </ul>                                                                                        | 10 mm                                  |
| <ul style="list-style-type: none"> <li>— downwards</li> </ul>                                                                                          | 10 mm                                  |
| <ul style="list-style-type: none"> <li>• for live parts <ul style="list-style-type: none"> <li>— forwards</li> </ul> </li> </ul>                       | 32 mm                                  |
| <ul style="list-style-type: none"> <li>— backwards</li> </ul>                                                                                          | 0 mm                                   |
| <ul style="list-style-type: none"> <li>— upwards</li> </ul>                                                                                            | 50 mm                                  |

|               |       |
|---------------|-------|
| — downwards   | 10 mm |
| — at the side | 10 mm |

#### Connections/ Terminals

##### type of electrical connection

- |                                     |                         |
|-------------------------------------|-------------------------|
| • for main current circuit          | spring-loaded terminals |
| • for auxiliary and control circuit | spring-loaded terminals |

#### Safety related data

|                                                      |                                                  |
|------------------------------------------------------|--------------------------------------------------|
| product function suitable for safety function        | Yes                                              |
| Electrical Safety                                    |                                                  |
| touch protection on the front according to IEC 60529 | finger-safe, for vertical contact from the front |

#### Communication/ Protocol

##### protocol is supported

- |                        |    |
|------------------------|----|
| • PROFINET IO protocol | No |
| • PROFI-safe protocol  | No |

|                                             |    |
|---------------------------------------------|----|
| protocol is supported AS-Interface protocol | No |
|---------------------------------------------|----|

#### Approvals Certificates

|             |                          |                                |
|-------------|--------------------------|--------------------------------|
| Environment | General Product Approval | For use in hazardous locations |
|-------------|--------------------------|--------------------------------|

[Environmental Confirmations](#)



#### Test Certificates

#### Maritime application

[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)



#### Maritime application

#### other



[Confirmation](#)

[Confirmation](#)



#### Railway

[Special Test Certificate](#)

#### Further information

##### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

##### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RA2210-0HH15-2AP0>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RA2210-0HH15-2AP0>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)



[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RA2210-0HH15-2AP0&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA2210-0HH15-2AP0&lang=en)

##### Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA2210-0HH15-2AP0>

##### Characteristic curves

[https://curves.siemens.com/curves/<mmp\\_prod\\_noCOMP=HAUPT"></mmp\\_prod\\_no>](https://curves.siemens.com/curves/<mmp_prod_noCOMP=HAUPT)



last modified:

4/24/2026 