

# Product datasheet

Specifications



Circuit breaker, MasterPacT MTZ2, UL 489, max 1600A rated, 3 pole, drawout mount, LF breaking cap, 600VAC

LV838921

ⓘ Discontinued

## Main

Product name	MasterPact MTZ2
Device short name	MTZ2 16 LF
Product or component type	Circuit breaker
Device application	Protection
Poles description	3P
Network type	AC
Network frequency	50/60 Hz
Breaking capacity code	LF

## Complementary

Control type	Push-button
Mounting mode	Drawout
Mounting support	Base plate Rails
[In] rated current	1600 A at 40 °C
Circuit breaker CT rating	1600 A
performance level	200 kA Icu at 240 V AC 50/60 Hz conforming to UL 489 150 kA Icu at 480 V AC 50/60 Hz conforming to UL 489 100 kA Icu at 600 V AC 50/60 Hz conforming to UL 489
Connection pitch	115 mm
[Icw] rated short-time withstand current	22 kA 0.5 s conforming to UL 489
Integral instant protection	49.5...55.5 kA
Rated breaking and making capacity	50 kA
Maximum breaking time	9 ms
Maximum closing response time	70 ms
Height	438.8 mm
Width	444.3 mm
Depth	426.8 mm

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

---

Package 1 Height	0.1 cm
Package 1 Width	0.1 cm
Package 1 Length	0.1 cm
Package 1 Weight	0.01 kg

---

## Contractual warranty

---

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

### Use Longer



#### Lifetime extension

Repair **No**

### Use Again



#### Repack and remanufacture

Take-back **No**