

Product datasheet

Specifications



switch-disconnector Compact NS100 NA - 100 A - 3 poles

29629

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

Main

Range of product	NS100...250
Range	ComPact
Product name	Compact NS100 NA
Device short name	Compact NS100 NA
Product or component type	Switch disconnector
Device application	Distribution
Poles description	3P
Network type	AC DC
Network frequency	50/60 Hz
[Ie] rated operational current	AC-22A: 100 A AC 50/60 Hz 220/240 V AC-22A: 100 A AC 50/60 Hz 380/415 V AC-22A: 100 A AC 50/60 Hz 440/480 V AC-22A: 100 A AC 50/60 Hz 500/525 V AC-22A: 100 A AC 50/60 Hz 660/690 V AC-23A: 100 A AC 50/60 Hz 220/240 V AC-23A: 100 A AC 50/60 Hz 380/415 V AC-23A: 100 A AC 50/60 Hz 440/480 V AC-23A: 100 A AC 50/60 Hz 500/525 V AC-23A: 100 A AC 50/60 Hz 660/690 V DC-22A: 100 A DC 250 V 1P DC-22A: 100 A DC 500 V 2 poles in series DC-23A: 100 A DC 250 V 1P DC-23A: 100 A DC 500 V 2 poles in series
[Ui] rated insulation voltage	750 V AC 50/60 Hz conforming to IEC 60947-3
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-3
[Ith] conventional free air thermal current	100 A at 60 °C
[Icm] rated short-circuit making capacity	2.6 kA
[Ue] rated operational voltage	500 V DC conforming to IEC 60947-3 690 V AC 50/60 Hz conforming to IEC 60947-3
Breaking capacity code	NA
Suitability for isolation	Yes conforming to IEC 60947-3
Contact position indicator	Yes
Visible break	No
Pollution degree	3 conforming to IEC 60947-3

Complementary

Control type	Toggle
Mounting mode	Fixed
Upside connection	Front
Downside connection	Front
[Icw] rated short-time withstand current	0.69 kA during 20 s conforming to IEC 60947-3 1.8 kA during 1 s conforming to IEC 60947-3 1.8 kA during 3 s conforming to IEC 60947-3
Mechanical durability	50000 cycles conforming to IEC 60947-3
Electrical durability	AC-22A: 50000 cycles 690 V AC 50/60 Hz conforming to IEC 60947-3 AC-23A: 30000 cycles 440 V AC 50/60 Hz conforming to IEC 60947-3 AC-23A: 50000 cycles 440 V AC 50/60 Hz In/2 conforming to IEC 60947-3 DC-23A: 30000 cycles 250 V DC conforming to IEC 60947-3 DC-23A: 50000 cycles 250 V DC In/2 conforming to IEC 60947-3
Connection pitch	35 mm
Height	161 mm
Width	105 mm
Depth	86 mm
Net weight	1.8 kg

Environment

Standards	IEC 60947-3
Product certifications	KEMA ASEFA ASTA
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins