

## References (continued) (1)

| Description                                                               | Type of connector | Length<br>m/ft | Item<br>(2) | Reference                          | Weight<br>kg/lb |
|---------------------------------------------------------------------------|-------------------|----------------|-------------|------------------------------------|-----------------|
| <b>X-bus preformed extension cordsets</b> with two 9-pin SUB-D connectors | Elbowed           | 0.8/2.63       | 8           | <a href="#">BMXXBC008K</a>         | 0.165/<br>0.364 |
|                                                                           |                   | 1.5/4.92       | 8           | <a href="#">BMXXBC015K</a>         | 0.250/<br>0.551 |
|                                                                           |                   | 3/9.84         | 8           | <a href="#">BMXXBC030K</a>         | 0.420/<br>0.926 |
|                                                                           |                   | 5/16.4         | 8           | <a href="#">BMXXBC050K</a>         | 0.650/<br>1.433 |
|                                                                           |                   | 12/39          | 8           | <a href="#">BMXXBC120K</a>         | 1.440/<br>3.175 |
|                                                                           | Straight          | 1/3.28         | 8           | <a href="#">TSXCBY010K</a>         | 0.160/<br>0.353 |
|                                                                           |                   | 3/9.84         | 8           | <a href="#">TSXCBY030K</a>         | 0.260/<br>0.573 |
|                                                                           |                   | 5/16.4         | 8           | <a href="#">TSXCBY050K</a>         | 0.360/<br>0.794 |
|                                                                           |                   | 12/39          | 8           | <a href="#">TSXCBY120K</a>         | 1.260/<br>2.778 |
|                                                                           |                   | 18/59          | 8           | <a href="#">TSXCBY180K</a>         | 1.860/<br>4.101 |
|                                                                           |                   | 28/92          | 8           | <a href="#">TSXCBY280KT</a><br>(3) | 2.860/<br>6.305 |

| Description                                                  | Use                                       | Length<br>m/ft | Item<br>(2) | Reference                  | Weight<br>kg/lb   |
|--------------------------------------------------------------|-------------------------------------------|----------------|-------------|----------------------------|-------------------|
| <b>Cable on reel</b><br>Cable with free ends, 2 line testers | To be equipped with 2 TSXCBYK9 connectors | 100/328        | —           | <a href="#">TSXCBY1000</a> | 12,320/<br>27.161 |

| Description                                                           | Use                                                                           | Sold in<br>lots of | Item<br>(2) | Reference                   | Weight<br>kg/lb |
|-----------------------------------------------------------------------|-------------------------------------------------------------------------------|--------------------|-------------|-----------------------------|-----------------|
| <b>Line terminator</b><br>2 x 9-way SUB-D connectors marked A/ and /B | Required on the 2 BM●XBP●●●0 modules located at either end of the daisy chain | 2                  | 9           | <a href="#">TSXTLYEX</a>    | 0.050/<br>0.110 |
| <b>X-bus straight connectors</b><br>2 x 9-way SUB-D connectors        | For TSXCBY1000 cable ends                                                     | 2                  | —           | <a href="#">TSXCBYK9</a>    | 0.080/<br>0.176 |
| <b>Connector installation kit</b><br>2 crimping pliers,<br>1 pen (4)  | For fixing TSXCBYK9 connectors                                                | —                  | —           | <a href="#">TSXCBYACC10</a> | —               |

(1) For additional characteristics, see our website [www.se.com](http://www.se.com).

(2) For items 1 to 4, see [page 5/14](#) and for items 5 to 7, see [page 5/15](#)

(3) Cable supplied with a set of 2 TSXTVSY100 electrical transient suppressors.

(4) Installation of connectors on the cable also requires a wire stripper, a pair of scissors, and a digital ohmmeter.