

Product data sheet

Specifications



ground fault protector GFP - 4 poles
- 100A - 240..480V - 300mA SIE

60999

⚠ Discontinued on: Nov 6, 2025

⚠ End-of-service on: Dec 31, 2025

⚠ Discontinued

Main

Range	Multi9
Product name	Multi9 GFP
Product or component type	Residual current circuit breaker (RCCB)
Device short name	GFP
Poles description	4P
Neutral position	Left
[In] rated current	100 A
Network type	AC
Earth-leakage sensitivity	300 mA
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type AC-SIE
Rated conditional short-circuit current	10 kA
Utilisation category	AC-22B

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	240 V AC 60 Hz 480Y/277 V AC 60 Hz 230/400 V AC 50 Hz 240/415 V AC 50 Hz
[Uimp] rated impulse withstand voltage	6 kV
Control type	Toggle
Local signalling	Fault indication
Connection pitch	0.7 in (18 mm) between phases
9 mm pitches	8
Colour	Grey
Mechanical durability	20000 cycles
Provision for padlocking	Padlockable
Locking options description	Padlocking in OFF position
Connections - terminals	Tunnel type terminals 0.004...0.05 in ² (2.5...35 mm ²) flexible Tunnel type terminals 0.004...0.05 in ² (2.5...35 mm ²) rigid
Wire stripping length	0.1 in (3.5 mm)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Standards	UL 1053 IEC 61008
IP degree of protection	IP20 conforming to IEC 60529 IP40 conforming to IEC 60529 IPxx B conforming to IEC 60529
Tropicalisation	2
Relative humidity	95 % 131 °F (55 °C)
Ambient air temperature for operation	-13...140 °F (-25...60 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.07 in (7.8 cm)
Package 1 Width	3.4 in (8.6 cm)
Package 1 Length	3.6 in (9.2 cm)
Package 1 Weight	12.3 oz (347.9 g)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
SCIP Number	A7b24ae6-2312-4e67-b7c9-56fce3e8c723
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins