

7MF0300-1TD01-5TM2-Z A00+C11+E48+H01+Y01



Image similar

SITRANS P320 Pressure transmitter Gauge pressure HART (4...20 mA) Measuring cell filling: Silicone oil Maximum measuring span: 63 bar (914 psi) Male thread G1/2 (DIN EN 837-1) Process connection: Stainless steel 316L/1.4404, Seal diaphragms: Stainless steel 316L/1.4404, Sensor differential pressure: Process flange: Stainless steel 316/1.4408 Die-cast aluminum housing Dual chamber device Intrinsic safety, Explosion proof, Dust ignition proof zone 21/22 (DIP), increased safety zone 2, class division 2 x 1/2-14 NPT With display (lid with glass window) Cable gland and sealing plug attached, plastic Quality inspection certificate - 5 point factory calibration (IEC 60770-2) CSA (Canada) & FM (USA) Mounting bracket, electrogalvanised steel Measuring range setting: Lower range value (max. 5 characters), Upper range value (max. 5 characters), Unit (mbar, bar, kPa, MPa, psi, ...) Example: -0.5 ... 10.5 psi (stainless steel plate)

Notes

Please enter text for every Y option (using the Configurator).

List Price	Show prices
Customer Price	Show prices
Repair & replacement services	For this product we offer a fast delivery and if possible an exchange or repair part. For further information please contact your local Spares&Repair Partner
Manuals, Certificates, FAQs...	Service & Support

Product

Article Number	7MF0300-1TD01-5TM2-Z A00+C11+E48+H01+Y01
Product Description	SITRANS P320 Pressure transmitter Gauge pressure HART (4...20 mA) Measuring cell filling: Silicone oil Maximum measuring span: 63 bar (914 psi) Male thread G1/2 (DIN EN 837-1) Process connection: Stainless steel 316L/1.4404, Seal diaphragms: Stainless steel 316L/1.4404, Sensor differential pressure: Process flange: Stainless steel 316/1.4408 Die-cast aluminum housing Dual chamber device Intrinsic safety, Explosion proof, Dust ignition proof zone 21/22 (DIP), increased safety zone 2, class division 2 x 1/2-14 NPT With display (lid with glass window) Cable gland and sealing plug attached, plastic Quality inspection certificate - 5 point factory calibration (IEC 60770-2) CSA (Canada) & FM (USA) Mounting bracket, electrogalvanised steel Measuring range setting: Lower range value (max. 5 characters), Upper range value (max. 5 characters), Unit (mbar, bar, kPa, MPa, psi, ...) Example: -0.5 ... 10.5 psi (stainless steel plate)
Product family	Gauge pressure (pressure series)
Product Lifecycle (PLM)	PM300:Active Product
Notes	Please enter text for every Y option (using the Configurator).

Price data

Price Group	8P1
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Material	see also metal factor (further details are available on the help page)
Metal Factor	see also metal factor (further details are available on the help page)

Delivery information

Export Control Regulations	ECCN : EAR99H / AL : N
Estimated dispatch time (Working Days)	20 Day(s)
Net Weight (kg)	1,800 Kg
Package size unit of measure	Not available
Quantity Unit	1 Piece
Packaging Quantity	1

Additional Product Information

EAN	Not available
UPC	Not available
Commodity Code	90262020
LKZ_FDB/ CatalogID	F101-1
Product Group	4770
Group Code	R3P0
Country of origin	France
Compliance with the substance restrictions according to RoHS directive	Since: 17.09.2018
Product class	C: products manufactured / produced to order, which cannot be reused or re-utilised or be returned against credit.
WEEE (2012/19/EU) Take-Back Obligation	Yes
REACH Art. 33 Duty to inform according to the current list of candidates	
SCIP number	Not available

Classifications

Version	Classification
---------	----------------