

surge suppressor, RC element, 400-600 V AC, 50/60 Hz, for contactors 3RT2.1 and auxiliary contactors 3RH2, multi-unit packaging, pack = 10 units

product brand name	SIRIUS
product category	Surge suppressor
product designation	RC element
suitability for use	for 3RT2.1 contactors and 3RH2 auxiliary contactors
<b>General technical data</b>	
certificate of suitability	CE / UL / CSA
size of contactor	S00
Substance Prohibition (day/month/year)	10/01/2009
SVHC substance name	Lead CAS-No. 7439-92-1
Net Weight	0.01 kg
type of voltage of the control supply voltage	AC
control supply voltage at AC	
• at 50 Hz rated value	400 ... 600 V
• at 60 Hz rated value	400 ... 600 V
control supply voltage frequency	
• 1 rated value	50 Hz
• 2 rated value	60 Hz
design of the surge suppressor	RC element
<b>Ambient conditions</b>	
ambient temperature	
• during operation	-25 ... +60 °C
• during storage	-40 ... +80 °C
<b>Installation/ mounting/ dimensions</b>	
mounting position	any
fastening method	clip-on
height	46 mm
width	28 mm
depth	9 mm
<b>Further information</b>	

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2916-1CF00-Z X90>

### Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2916-1CF00-Z X90>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2916-1CF00-Z X90>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2916-1CF00-Z X90&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2916-1CF00-Z X90&lang=en)



