



Figure similar

SIPLUS S7-300 SM 331 4AI based on 6ES7331-7RD00-0AB0 with conformal coating, -25...+70 °C, (70° only 4-wire),

| General information | |
|---|---|
| based on | 6ES7331-7RD00-0AB0 |
| Supply voltage | |
| Load voltage L+ | |
| <ul style="list-style-type: none"> Rated value (DC) Reverse polarity protection | 24 V Yes |
| Input current | |
| from load voltage L+ (without load), max. | 250 mA |
| from backplane bus 5 V DC, max. | 60 mA |
| Output voltage | |
| Power supply to the transmitters | |
| <ul style="list-style-type: none"> Rated value (DC) | 13 V; at 22 mA |
| Power loss | |
| Power loss, typ. | 3 W |
| Analog inputs | |
| Number of analog inputs | 4 |
| permissible input current for current input (destruction limit), max. | 40 mA |
| Input ranges | |
| <ul style="list-style-type: none"> Voltage Current Thermocouple Resistance thermometer Resistance | No Yes No No No |
| Input ranges (rated values), currents | |
| <ul style="list-style-type: none"> 0 to 20 mA — Input resistance (0 to 20 mA) 4 mA to 20 mA — Input resistance (4 mA to 20 mA) | Yes 50 Ω Yes 50 Ω |
| Cable length | |
| <ul style="list-style-type: none"> shielded, max. | 200 m |
| Analog value generation for the inputs | |
| Integration and conversion time/resolution per channel | |
| <ul style="list-style-type: none"> Resolution with overrange (bit including sign), max. Integration time, parameterizable Interference voltage suppression for interference frequency f_1 in Hz | 16 bit; 10 bit to 15 bit + sign Yes; 2.5 to 100 ms 10 to 400 Hz |
| Encoder | |

| | |
|---|---|
| Connection of signal encoders | |
| • for current measurement as 2-wire transducer | Yes |
| • for current measurement as 4-wire transducer | Yes |
| Errors/accuracies | |
| Operational error limit in overall temperature range | |
| • Current, relative to input range, (+/-) | 0.45 % |
| Basic error limit (operational limit at 25 °C) | |
| • Current, relative to input range, (+/-) | 0.1 % |
| Interrupts/diagnostics/status information | |
| Diagnostics function | Yes |
| Diagnoses | |
| • Diagnostic information readable | Yes |
| • Overrange | Yes |
| • Wire-break in signal transmitter cable | Yes |
| • Short-circuit of the signal encoder cable | Yes |
| Diagnostics indication LED | |
| • Group error SF (red) | Yes |
| • Channel fault indicator F (red) | Yes |
| Ex(i) characteristics | |
| Module for Ex(i) protection | Yes |
| maximum values for connecting terminals for gas group IIC | |
| • U _o (no-load voltage), max. | 25.2 V |
| • I _o (short-circuit current), max. | 68.5 mA |
| • P _o (power output), max. | 431 mW |
| • C _o (permissible external capacity), max. | 90 nF |
| • L _o (permissible external inductivity), max. | 7.5 mH |
| Standards, approvals, certificates | |
| CE mark | Yes |
| UL approval | Yes; File E239877 |
| RCM (formerly C-TICK) | Yes |
| KC approval | Yes |
| EAC (formerly Gost-R) | Yes |
| Use in hazardous areas | |
| • ATEX marking | ATEX II 3 G (2) GD Ex nA [ib Gb] [ib IIIC Db] IIC T4 Gc |
| • FM marking | Class I, Division 2, Group A, B, C, D T4 |
| • Test number PTB | Ex-96.D.2092X |
| Railway application | |
| • EN 50121-4 | No |
| • EN 50155 | No |
| Ambient conditions | |
| Ambient temperature during operation | |
| • min. | -25 °C; = T _{min} |
| • max. | 60 °C; = T _{max} ; 60 °C @ UL/cUL, ATEX and FM use, 70 °C only 4 wire |
| Ambient temperature during storage/transportation | |
| • min. | -40 °C |
| • max. | 70 °C |
| Altitude during operation relating to sea level | |
| • Installation altitude above sea level, max. | 5 000 m |
| • Ambient air temperature-barometric pressure-altitude | T _{min} ... T _{max} at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // T _{min} ... (T _{max} - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // T _{min} ... (T _{max} -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m) |
| Relative humidity | |
| • With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation/frost (no commissioning under condensation conditions) |
| Resistance | |
| Use in stationary industrial systems | |
| — to biologically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request |
| — to chemically active substances according to EN 60721-3-3 | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |

| | |
|---|---|
| — to mechanically active substances according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust, * |
| Use on ships/at sea | |
| — to biologically active substances according to EN 60721-3-6 | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request |
| — to chemically active substances according to EN 60721-3-6 | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-6 | Yes; Class 6S3 incl. sand, dust; * |
| Usage in industrial process technology | |
| — Against chemically active substances acc. to EN 60654-4 | Yes; Class 3 (excluding trichlorethylene) |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) |
| Remark | |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04 | * The supplied plug covers must remain in place over the unused interfaces during operation! |

Connection method

| | |
|--------------------------|--------|
| required front connector | 20-pin |
|--------------------------|--------|

Dimensions

| | |
|--------|--------|
| Width | 40 mm |
| Height | 125 mm |
| Depth | 120 mm |

Weights

| | |
|-----------------|-------|
| Weight, approx. | 290 g |
|-----------------|-------|

Classifications

| | Version | Classification |
|--------|---------|----------------|
| eClass | 14 | 27-24-22-01 |
| eClass | 12 | 27-24-22-01 |
| eClass | 9.1 | 27-24-22-01 |
| eClass | 9 | 27-24-22-01 |
| eClass | 8 | 27-24-22-01 |
| eClass | 7.1 | 27-24-22-01 |
| eClass | 6 | 27-24-22-01 |
| ETIM | 10 | EC001420 |
| ETIM | 9 | EC001420 |
| ETIM | 8 | EC001420 |
| ETIM | 7 | EC001420 |
| IDEA | 4 | 3562 |
| UNSPSC | 15 | 32-15-17-05 |

Approvals / Certificates

| | |
|---------------------------------|------------|
| General Product Approval | EMV |
|---------------------------------|------------|

[Manufacturer Declaration](#)

[China RoHS](#)



last modified:

7/1/2025