

# Product datasheet

Specifications

## Domae - comb busbar - 3L+N - 18 mm pitch - 12 modules - 60A



MGN10556

⚠ Discontinued on: 27 Feb 2021

EAN Code: 3606481969279

⚠ Discontinued

### Main

Range	Domae
Product or component type	Comb busbar
Mounting mode	Horizontal
Accessory / separate part category	Connection accessory
Lines description	3L + N
Length in 18 mm modules	12

### Complementary

Number of ways	Incomer: 1 way N + 3 L Outgoer 1: 3 ways L Outgoer 2: 5 ways N + L
Poles configuration for 1 way	Incomer: 1 x 3P + N Outgoer 1: 1 x 1P Outgoer 2: 1 x 1P + N
Connection pitch	Incomer: 18 mm Outgoer 1: 18 mm Outgoer 2: 9 mm
Connector type	Incomer: fork Outgoer 1: fork Outgoer 2: tooth
Distance between way	Incomer: 72 mm Outgoer 1: 18 mm Outgoer 2: 18 mm
Insulation	Insulated
Device presentation	Uncuttable
[Ie] rated operational current	60 A at 40 °C
[Ue] rated operational voltage	230 V AC Ph/N 400 V AC Ph/Ph
[Ui] rated insulation voltage	500 V AC
Mounting location	Bottom on tunnel type terminals Bottom on biconnect
9 mm pitches	24
Width	220 mm
Colour	Light grey (RAL 7035)
Range compatibility	Acti 9 Acti9 iDPN Acti 9 Acti9 K60 Acti 9 Acti9 ID K

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	3 cm
Package 1 Length	22 cm
Package 1 Weight	250 g



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

Packaging made with recycled cardboard

Yes

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins