

Product data sheet

Specifications



Wear part, enclosure door, fan for variable speed drive, Altivar Process 600 900, from 110 to 315kW, from 380 to 440V

VX5VPM002

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range Compatibility	Altivar Process 600/900
Accessory / Separate Part Type	Enclosure door fan
Accessory / separate part category	Cooling accessory
Product or Component Type	Fan
Net Weight	1.8 lb(US) (0.8 kg)

Complementary

Kit composition	Fan Mounting bracket Instruction sheet
-----------------	--

Product compatibility	Variable speed drive ATV630 floor-standing 110 kW 380...440 V Variable speed drive ATV630 floor-standing 132 kW 380...440 V Variable speed drive ATV630 floor-standing 160 kW 380...440 V Variable speed drive ATV630 floor-standing 200 kW 380...440 V Variable speed drive ATV630 floor-standing 250 kW 380...440 V Variable speed drive ATV630 floor-standing 315 kW 380...440 V Variable speed drive ATV650 floor-standing 110 kW 380...440 V Variable speed drive ATV650 floor-standing 132 kW 380...440 V Variable speed drive ATV650 floor-standing 160 kW 380...440 V Variable speed drive ATV650 floor-standing 200 kW 380...440 V Variable speed drive ATV650 floor-standing 250 kW 380...440 V Variable speed drive ATV650 floor-standing 315 kW 380...440 V Variable speed drive ATV930 floor-standing 110 kW 380...440 V Variable speed drive ATV930 floor-standing 132 kW 380...440 V Variable speed drive ATV930 floor-standing 160 kW 380...440 V Variable speed drive ATV930 floor-standing 200 kW 380...440 V Variable speed drive ATV930 floor-standing 250 kW 380...440 V Variable speed drive ATV930 floor-standing 315 kW 380...440 V Variable speed drive ATV950 floor-standing 110 kW 380...440 V Variable speed drive ATV950 floor-standing 132 kW 380...440 V Variable speed drive ATV950 floor-standing 160 kW 380...440 V Variable speed drive ATV950 floor-standing 200 kW 380...440 V Variable speed drive ATV950 floor-standing 250 kW 380...440 V Variable speed drive ATV950 floor-standing 315 kW 380...440 V
-----------------------	--

Ordering and shipping details

Category	US1CP4E22280
Discount Schedule	CP4E
GTIN	3606485406831
Returnability	No
Country of origin	FR

Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.622 in (9.200 cm)
Package 1 Width	12.008 in (30.500 cm)
Package 1 Length	11.811 in (30.000 cm)
Package weight(Lbs)	28.148 oz (798.000 g)
Unit Type of Package 2	S04
Number of Units in Package 2	3
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	15.748 in (40.000 cm)
Package 2 Length	23.622 in (60.000 cm)
Package 2 Weight	7.992 lb(US) (3.625 kg)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No