


Product datasheet

Specifications



coil WB1-K - 380...415 V AC 40...400 Hz

WB1KB139

⚠ Discontinued on: 9 Feb 2022

⚠ Discontinued

Main

Range	TeSys
Product or component type	Contactor coil
Range compatibility	TeSys TeSys B CR1B contactor
[Uc] control circuit voltage	380...440 V AC 50...400 Hz

Complementary

Control circuit voltage limits	190...221 V at 50...400 Hz
Inrush power in VA	450...620 VA 1P
Inrush power in W	380...520 W for 1P
Hold-in power consumption in VA	0.15...0.2 VA 50...400 Hz 1P
Hold-in power consumption in W	0.15...0.2 W for 1P
Mechanical durability	1200000 cycles

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9 cm
Package 1 Width	7 cm
Package 1 Length	17 cm
Package 1 Weight	1.15 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
EU RoHS Directive	Compliant

Use Longer

Lifetime extension	
Repair	No