



### Main

|                               |  |
|-------------------------------|--|
| Range of Product              | Telemecanique Photoelectric sensors XU |
| Series name                   | Application                            |
| Electronic sensor type        | Photo-electric sensor                  |
| Sensor name                   | XUY                                    |
| Sensor design                 | Fiber design                           |
| Detection system              | Through beam                           |
| Material                      | Metal                                  |
| Type of output signal         | Discrete                               |
| Supply circuit type           | DC                                     |
| Wiring Technique              | 3-wire                                 |
| Discrete output type          | PNP or NPN                             |
| Discrete output function      | 1 NO or 1 NC programmable              |
| Electrical connection         | 1 remote male connector M12, 4 pins    |
| Cable length                  | 0.98 ft (0.3 m)                        |
| Product Specific Application  | Conveyor system                        |
| Emission                      | Infrared                               |
| [Sn] nominal sensing distance | 0.33 ft (0.1 m) diffuse                |

### Complementary

|                           |  |
|---------------------------|--|
| Enclosure Material        | Aluminum                                       |
| Lens material             | Polycarbonate                                  |
| Cover Material            | PVC  |
| Pulse frequency           | 1 kHz  |
| Output Type               | Solid state                                    |
| Status LED                | 1 LED Yellow output signal                     |
| [Us] rated supply voltage | 24 V DC reverse polarity protection            |
| Supply voltage limits     | 18...30 V DC                                   |
| Switching capacity in mA  | 100 mA (overload and short-circuit protection) |
| Switching frequency       | 500 Hz   |
| Maximum voltage drop      | <2 V (100 mA closed state)                     |
| Current consumption       | < 35 mA no-load                                |
| Maximum delay response    | 1 ms   |
| Diameter                  | 0.47 in (12 mm)                                |
| Length                    | 16.14 in (410 mm)                              |
| Net Weight                | 0.14 lb(US) (0.065 kg)                         |

### Environment

|                                       |                           |
|---------------------------------------|---------------------------|
| Product Certifications                | CE                        |
| Ambient Air Temperature for Operation | 14...131 °F (-10...55 °C) |
| Ambient Air Temperature for Storage   | -4...176 °F (-20...80 °C) |
| IP degree of protection               | IP50 IEC 60529            |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Ordering and shipping details

|                       |                              |
|-----------------------|------------------------------|
| Category              | 22481-SENSORS, PHOTOELECTRIC |
| Discount Schedule     | DS2                          |
| GTIN                  | 3389119019910                |
| Nbr. of units in pkg. | 1                            |
| Package weight(Lbs)   | 1.20 oz (34.0 g)             |
| Returnability         | No                           |
| Country of origin     | FR                           |

## Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | PCE                    |
| Package 1 Height             | 0.79 in (2 cm)         |
| Package 1 width              | 0.79 in (2 cm)         |
| Package 1 Length             | 2.36 in (6 cm)         |
| Unit Type of Package 2       | S01                    |
| Number of Units in Package 2 | 50                     |
| Package 2 Weight             | 4.24 lb(US) (1.925 kg) |
| Package 2 Height             | 5.91 in (15 cm)        |
| Package 2 width              | 5.91 in (15 cm)        |
| Package 2 Length             | 15.75 in (40 cm)       |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| California proposition 65  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|