



Representative Image

### Catalog No. TLM4222CCUG

**Description:** 225A 42CT 1P3W 22K IC FLD CONV WGRND BR

**UPC No** 783164158700

**Home > Load Centers > Load Centers**

PowerMark Gold convertible load centers arrive as main lug, but have the capability to have a main breaker installed. All ABB load centers are rated up to 60 degree/75 degree centigrade and is suitable for use with service entrance equipment when installed in accordance with electrical code. The TLM4222CCUG features space for 42, 1" breakers, 225 A bus ampere rating, a copper bus, a factory installed ground bar, and a combination/flush enclosure.

#### Descriptors

Category	Load Centers
Grouping	Single Phase - USA

#### Specifications

Load Center Type	Standard
Input/Output Voltage	120/240V ac
Amperage	225 A
Device type	Main Lug
Enclosure	Indoor
Phase	1 Phase
1" Space	42
1/2" Space	0
Feed	Either
Door	Yes
Circuit Breaker Style	Plug-In
NEMA Rating	NEMA 1
Factory Installed Ground Kit	Yes
Enclosure Type	Indoor, Combination

#### Classifications

UL/CUL Listing	UL
----------------	----



## Publications

Title	Publication No.	Publication Type
<a href="#">Section 1 BuyLog: Load centers and circuit breakers</a> Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line.	DET1023	Application and Technical

**Additional Documentation:** Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.